

ICS 91.140.80
CCS P 42

CJ

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

CJ/T 278-2008

Polypropylene pipe and fitting for drainage inside buildings

建筑排水用聚丙烯（PP）管材和管件

(English Translation)

Issued on: June 3, 2008

Implemented on: November 1, 2008

**Issued by: Ministry of Housing and Urban-Rural Development of the
People's Republic of China**

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard provides a polypropylene (PP) resin as the main raw material for the production of building sewage, waste water discharge pipe (hereinafter referred to as " pipe "), symbols and abbreviations pipe fittings, raw materials, product classification, requirements, test methods, inspection rules, marking, packaging, transportation and storage. This standard applies to building sewage, wastewater gravity drainage and buried pipelines. In considering the materials, chemical resistance and heat resistance conditions, can also be used for industrial drainage pipe. This standard specifies the temperature of the fluid inside the pipe application range 0°C ~ 65°C, instantaneous drainage temperature does not exceed 95°C.

Document data

International classification (ICS): 91.140.80.

Chinese classification (CCS): P42.

Estimated length of the Chinese original: 30,349 words.

Adopted international standard: EN 1451.1-2000, NEQ; EN 1053-1995, NEQ; EN 1054-1995, NEQ; EN 1055-1996, NEQ.

Standards quoted by this document

GB/T 2828.1; GB/T 2918; GB/T 3682; GB/T 6111; GB/T 667; GB/T 8803; GB/T 8806; GB/T 9647; GB/T 14152; GB/T 17391; GB/T 19472.1; HG/T 3091; EN 1053: 1995; EN 1054: 1995; EN 1055