

ICS 91.140
CCS P 45

CJ

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

CJ/T 392-2012

Replacing CJ/T 3030-1995

Commercial gas oven for cooking

炊用燃气大锅灶

(English Translation)

Issued on: January 1, 1970

Implemented on: January 1, 1970

**Issued by: Ministry of Housing and Urban-Rural Development of the
People's Republic of China**

Table of Contents

Preface

1 Scope

2 Normative references

3 Terms and definitions

4 Classification and model

5 Structure and materials

6 Performance Requirements

7 Test Method

Inspection rules

9 Logos, warnings and instructions

10 Packaging, transportation and storage

Appendix A (informative) This standard uses the provisions of the basic requirements of GB 16914-2003 Table

Foreword

This standard was drafted in accordance with the rules given in GB/T 1.1-2009.

This standard replaces CJ/T 3030-1995 "cooking gas cookers." this standard is the revision of CJ/T 3030-1995 "cooking gas cookers", compared with the CJ/T 3030-1995 main technical changes as follows.

--- Increased flame monitoring device (see Table 1);

--- Increased electrical performance (see Table 1);

--- Supplement the structural requirements (see 5.1, 1995 edition 4.1.8, 4.2);

--- Modify the combustion noise (see Table 1, 1995 edition of Table 3).

This standard uses the redrafted Law Reference BSEN203-1.:2005/A1..2008 "Gas Common Catering Equipment General Safety Rules" Consistency with EN203.:2005 is not equivalent.

This standard is consistent with the GB 16914-2003 "gas burning appliances safety conditions" is given in Appendix A of this standard mining with GB 16914-2003 the basic requirements of the corresponding table.

This standard proposed by the Ministry of Housing and Urban Standard and Design

Institute.

This standard by the Ministry of Housing and Urban-township gas standard technical focal points centralized.

This standard was drafted. Beijing Institute of Public Utilities, Yu-kitchen equipment (Shenzhen) Co., Ltd., Beijing police shield Jingxi kitchen Room Equipment Co., Ltd., Zhejiang Cheung Ying Kitchen Equipment Co., Ltd., Beijing Jingcheng Kitchen Equipment Co., Ltd., Beijing Xing Ye Sheng Kitchen Limited company.

1 Scope

This standard specifies the terms and definitions of cooking gas cookers, classification and type, structure and materials, performance requirements, test methods, testing Rules, logos, warnings and instructions, packaging, shipping and storage.

This standard applies to a single stove eye rated heat load of not more than 80kW, the nominal diameter of the pot is not less than 600mm of cooking gas cauldron Stove (hereinafter referred to as the pot stove).

2 Normative references

The following documents for the application of this document is essential. For dated references, only the dated version applies to this article Pieces. For undated references, the latest edition (including all amendments) applies to this document.

GB/T 191 Packaging - Pictorial signs GB/T 2828.2 Sampling procedures for sampling inspection - Part 2. Isolated lot inspection sampling plan by limit mass (LQ) GB/T 3768 Acoustics sound pressure method for the determination of noise source sound power level above the reflective surface using envelope measurement of surface simple method GB 4706.1 Safety of household and similar electrical appliances - Part 1. General requirements GB/T 7306 (all parts) 55 ° sealing pipe thread GB/T 7307 55 ° non-sealed pipe thread GB/T 13611 urban gas classification and basic characteristics Household gas appliances GB/T 16411-2008 General test methods Gas burning appliances safety technical conditions

3 Terms and definitions

The following terms and definitions apply to this document.

Use of urban gas-based energy, closed or semi-enclosed metal assembly furnace, and the pot is fixed or tiltable large-scale cooking Zaoju.

Reference status referenceconditions the temperature is 15 °C, the absolute pressure is 101.3kPa dry gas conditions.

[GB/T 16411-2008, Definition 3.1] 3.3 Coldstate Means the reference gas conditions, the

rated pressure state, the normal ignition large pot, the gas supply to normal after the stop running until the burner cooling Close to room temperature after the state.

Hotstate

Is the reference gas conditions, the rated pressure state, the normal ignition cooker, running 15min after the state.