

ICS 91.140.60  
CCS P 42

**CJ**

**INDUSTRY STANDARD OF THE  
PEOPLE'S REPUBLIC OF CHINA**

**CJ/T 488-2016**

---

**Steel-plastic complex pipes of short pitch internal spiral rib for  
drainage inside buildings  
(English Translation)**

**Issued on: June 14, 2016**

**Implemented on: December 1, 2016**

---

**Issued by: Ministry of Housing and Urban-Rural Development of the  
People's Republic of China**

## Table of Contents

|                                         |   |
|-----------------------------------------|---|
| What this standard covers .....         | 1 |
| Document data .....                     | 2 |
| Standards quoted by this document ..... | 3 |

### What this standard covers

This standard specifies the terms and definitions, materials, requirements, test methods, inspection rules and marking, packaging, transportation and storage of building drainage steel-plastic composite, plastic short pitch inner spiral. This standard applies to civil construction drainage system riser of steel-plastic composite, plastic short pitch within the pitch pipe. (PVC-U) material for water temperature 0°C ~ 45°, instantaneous drainage temperature does not exceed 60°C; high-density polyvinyl chloride (HDPE), the temperature of the drainage system is different from that of the inner lining and the plastic material. And polypropylene (PP) material for water temperature 0°C ~ 65°, instantaneous drainage temperature does not exceed 90°C.

### Document data

International classification (ICS): 91.140.60.

Chinese classification (CCS): P42.

Estimated length of the Chinese original: 13,175 words.

### Standards quoted by this document

GB/T 246; GB/T 1033.1; GB/T 2102; GB/T 2828.1; GB/T 2918; GB/T 3091; GB/T 3682; GB/T 5836.1; GB/T 6111; GB/T 6671; GB/T 8802; GB/T 8804.2; GB/T 8806; GB/T 9647; GB/T 13526; GB/T 14152; GB 50242; CJ/T 250; CJ/T 278; HG/T 3349; HG/T 3668; QB/T 2803