

ICS 27.100
CCS K 48

DL

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

DL/T 1000.2-2015

Replacing DL/T 1000.2-2006

**Application guide of insulators for overhead lines with a
nominal voltage over 1000V Part 2: Ceramic or glass insulator
for d.c.system**

标称电压高于1000V架空线路用绝缘子使用导则 第2部分：直流系统用瓷或玻璃
绝缘子

(English Translation)

Issued on: July 1, 2015

Implemented on: December 1, 2015

Issued by: National Energy Administration

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard specifies the general technical requirements, selection principles, inspection, acceptance, on-site storage and transportation, installation, operation and maintenance of DC overhead line insulators with a nominal voltage higher than 1500V. This standard is applicable to DC overhead lines with a nominal voltage higher than 1500V, suspended porcelain or glass insulators (referred to as insulators) for converter stations. Installation location of the altitude of 1000m below the ambient temperature of -40°C ~ +40°.

Document data

International classification (ICS): 27.100.

Chinese classification (CCS): K48.

Estimated length of the Chinese original: 16,177 words.

Supersedes the earlier edition DL/T 1000.2-2006.

Standards quoted by this document

GB 311.1; GB/T 772; GB/T 775.3; GB/T 16927.1; GB/T 19443-2004; GB/T 2900.5; GB/T 2900.8; GB/T 4056; GB/T 24623; GB/T 25318; GB/T 26218.1; DL/T 626; JB/T 4307; JB/T 8177; JB/T 8178; JB/T 9677; JB/T 9678