

ICS 29.020
CCS K 48

DL

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

DL/T 383-2010

**Artificial heavy rain test method for high voltage bushing under
pollution condition
(English Translation)**

Issued on: January 9, 2011

Implemented on: May 1, 2011

Issued by: National Energy Administration

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard specifies the communication system with high pressure ceramic casing filthy conditions in artificial rain test methods under the general provisions of filthy substances, sample preparation, selection and determination of the degree of contamination, the test installation, test procedures and so on. This standard applies to outdoor filthy environmental conditions are rated at 110kV-300kV porcelain bushing (including hollow porcelain insulators) performance tests. This standard for organic composite casing (including hollow composite insulators) in addition to a number of special provisions supplement (see Appendix A), the other may refer to this standard test. In addition to the standard test of the DC power supply bushing special requirements, the other can also refer to the standard tests. This standard does not apply to horizontal mounting wall bushing.

Document data

International classification (ICS): 29.020.

Chinese classification (CCS): K48.

Estimated length of the Chinese original: 10,152 words.

Standards quoted by this document

GB/T 775.2-2003; GB/T 4585-2004; GB/T 16927.2-1997; GB/T 22707-2008