

ICS 29.120.40
CCS K 64



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB 15092.1-2010

Replacing GB/T 15092.1-2010

Switches for appliances - Part 1: General requirements

器具开关 第1部分：通用要求

(English Translation)

Issued on: December 14, 2020

Implemented on: July 1, 2021

Issued by: State Administration for Market Regulation

Table of Contents

Preface	
1 Scope	
2 Normative references	
3 Terms and Definitions	
4 Total requirements	
5 General precautions for testing	
6 Rating	
7 Categories	
8 Signs and documents	
9 Protection against electric shock	
10 Grounding device	
11 Terminals and terminals	
12 Structure	
13 Institutions	
14 Protection against solid foreign objects, water and moisture	
15 Insulation resistance and dielectric strength	
16 Fever	
17 Durability	
18 Mechanical strength	
19 Screws, current carriers and couplings	
20 Clearances, Creepage Distances, Solid Insulation and Coatings of Rigid Printed Circuit Board Components	
21 Fire hazard	
22 Anti-rust	
23 Abnormal operation and fault conditions of switches	
24 Switching components	
25 Electromagnetic compatibility (EMC) requirements	
Appendix A (Informative appendix) Common end product standards	
Appendix B (Normative appendix) Relationship between rated impulse withstand voltage, rated voltage and overvoltage category	
Appendix C (Normative appendix) Pollution level	
Appendix D (Normative appendix) Routine test	
Appendix E (Informative appendix) Sampling test	

Appendix F (Informative appendix) Switch Application Guidelines
Appendix G (Informative) Types of Coating for Rigid Printed Circuit Board Components
Appendix H (Informative appendix) Dimensions of the switch insert part
Appendix (Normative Appendix) Measurement of clearances and creepage distances
Appendix J (Informative appendix) Diagram for determining clearances and creepage distances
Appendix K (Normative appendix) Impulse voltage test
Appendix L (Normative appendix) Altitude correction factor
Appendix M (Normative appendix) Electric tracking resistance test
Appendix N (Normative appendix) Measuring the insulation distance of printed circuit boards with Type 1 coating
Appendix O (Normative appendix) Switch family
Reference
V~ switch test with capacitive load test circuit parameter value

1 Scope 1

2 Normative references 1
3 Terms and Definitions 3 4 total requirements 12
5 General precautions for testing 12 6 rating 13 7 categories 14
8 Signs and documents 26
9 Protection against electric shock 32
10 Grounding device 33
11 Terminals and terminals 35
12 Structure 39
13 institutions 40
14 Protection against solid foreign objects, water and moisture 41
15 Insulation resistance and dielectric strength 42
16 Fever 44

17 Durability46

18 Mechanical strength 46

19 Screws, current carriers and couplings 47

20 Clearances, Creepage Distances, Solid Insulation and Coatings of Rigid Printed Circuit Board Components 49

21 Fire hazard 55

22 anti-rust 56

23 Abnormal operation and fault conditions of switches 57 24 switching components 57

25 Electromagnetic compatibility (EMC) requirements 59

Appendix A

(Informative appendix) Common end product standards 72 Appendix B (Normative appendix) Relationship between rated impulse withstand voltage, rated voltage and overvoltage category 73 Appendix C (Normative appendix) Pollution level 74 Appendix D (Normative appendix) Routine test 75 Appendix E (Informative appendix) Sampling test 76 Appendix F (Informative appendix) Switch Application Guidelines 77 Appendix G (Informative) Types of Coating for Rigid Printed Circuit Board Components 79 Appendix H (Informative appendix) Dimensions of the switch insert part 80 Appendix I (Normative appendix) Measurement of clearances and creepage distances 81 Appendix J (Informative appendix) Diagram for determining clearances and creepage distances 85 Appendix K (Normative appendix) Impulse voltage test 86 Appendix L (Normative appendix) Altitude correction factor 87 Appendix M (Normative appendix) Electric tracking resistance test 88 Appendix N (Normative appendix) Measuring the insulation distance of printed circuit boards with Type 1 coating 89 Appendix O (Normative appendix) Switch family 90 Reference 92

Figure 1 Example of post terminal 62

Figure 2 Screw terminal and screw terminal example 63

Figure 3 Example of saddle terminal 64

Figure 4 Example of Lug Terminals 64

Figure 5 Example of a sleeve terminal 64

Figure 6 Example of screwless terminal 65

Figure 7 Test socket 66 for flat quick-connect terminals

Figure 8 Test circuit for AC capacitive load and simulated tungsten bulb load 66

Figure 9 Test circuit for DC capacitive load and simulated light bulb load 67

Figure 10 Rated at 10/100

V~ switch test with capacitive load test circuit parameter value	67
Figure 11 Installation device	68 for impact test
Figure 12 Continuous work --- working system S1 (see 7.18.1)	69
Figure 13 Short-time work --- work system S2 (see 7.18.2)	69
Figure 14 Intermittent cycle work --- work system S3 (see 7.18.3)	70
Figure 15 Heating test circuit diagram	70
Figure 16 Endurance test circuit diagram	71
Figure J.1 Schematic diagram for determining clearances and creepage distances	85
Figure N.1 Measurement of insulation distance	89
Table 1 Test load of multi-directional switch	13
Table 2 Switch type and connection mode	18
Table 3 Switch data and group load	26
Table 4 Resistive current carried by the terminal and the corresponding cross-sectional area of the connecting non-prepared conductor	35
Table 5 Terminal test sequence	37
Table 6 Pulling force of screw-type terminals	38
Table 7 Minimum insulation resistance	43
Table 8 Dielectric Strength	43
Table 9 minimum pulling force	46
Table 10 Torque value	48
Table 11 Torque values for threaded sealing caps	49
Table 12 Basic insulation minimum electrical clearance	50
Table 13 Basic insulation minimum creepage distance	52
Table 14 Working insulation minimum creepage distance	53
Table 15 Test levels and conditions	55
Table 16 Minimum requirements for capacitors	59
Table 17 Test level and duration of voltage dips and short interruptions	60
Table 18 Fast Transient Burst	61
Table B.1 Rated Impulse Withstand Voltage of Switches Directly Powered by Low Voltage	