

ICS 35.110
CCS L 78



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB 15629.11-2003

**[Including 2006XG1] Information technology -- Telecommunications and information
exchange between systems -- Local and metropolitan area networks -- Specific
requirements -- Part 11: Wireless LAN Medium access control (MAC) and physical layer
(PHY) specif**

信息技术 系统间远程通信和信息交换 局域网和城域网 特定要求 第11部分:无线局
域网媒体访问控制和物理层规范

(English Translation)

Issued on: May 12, 2003

Implemented on: December 1, 2003

**Issued by: General Administration of Quality Supervision, Inspection and
Quarantine of the People Republic of China**

Table of Contents

Preface	
Introduction	
1 Summary	
1.1 Scope	
1.2 Purpose	
2 normative reference document	
3 Terms and definitions	
4 Abbreviations	
5 General description	
5.1 General description of the architecture	
5.1.1 how the wireless network is different	
5.2 Components of this part of the system	
5.2.1 Independent BSS as adhoc network	
5.2.2 Distributed System Concepts	
5.2.3 Regional Concepts	
5.3 Logical service interface	
5.3.1 STA Service (SS)	
5.3.2 Distributed System Services (DSS)	
5.3.3 Multi-logical address space	
5.4 Service Overview	
5.4.1 Message Distribution within DS	
5.4.2 Services to support distributed services	
5.4.3 Access and Confidentiality Control Service	
5.5 Relationship between services	
5.5.1 Type 1 frames (both states 1, 2, 3 and 4 are allowed)	
5.5.2 Type 2 frames (if and only if the link authentication states 2, 3, 4 are allowed)	
5.5.3 Class 3 frames (if and only if the associated states 3, 4 are allowed)	
5.5.4 Type 4 frames (if and only if the authenticated state 4 is allowed)	
5.7 Message content for support services	
5.7.1 Data	
5.7.2 Associations	
5.7.3 Reassociation	

5.7.4 Disassociation	
5.7.5 Confidentiality	
5.7.6 Link Authentication	
5.7.7 Unlocking Link Authentication	
5.8 Reference model	
6 MAC Service Definition	
6.1 Overview of MAC services	
6.1.1 Asynchronous Data Service	
6.1.2 Security services	
6.1.3 MSDU Sorting	
6.2 Detailed Service Specification	
6.2.1 MAC Data Service	
7 frame format	
7.1 MAC frame format	
7.1.1 Conventions	
7.1.2 General frame format	
7.1.3 frame field	
7.2 Independent Type Frame Format	
7.2.1 Control frame	
7.2.2 Data frame	
7.2.3 Managing frames	
7.3 Management frame frame component	
7.3.1 Fixed field	
7.3.2 Information Element	
8.1 Identification Service	
8.1.1 System and port	
8.1.2 Controlled and uncontrolled access	
8.2 Authentication Service Unit (ASU)	
8.2.1 Public key certificate	
8.2.2 Public key certificate management	
8.2.3 Elliptic Curve Digital Signature Algorithm	
8.3 WAI Identification Infrastructure	
8.3.1 secure access	
8.3.2 WAI data format	
8.4 WPI Confidentiality Infrastructure	

- 8.5 Safety-related Management Information Base
 - 8.5.1 MIB attributes associated with authentication
 - 8.5.2 MIB attributes related to confidentiality
- 8.6 ad hoc network (adhoc) mode
- 9 MAC sublayer function
 - 9.1 MAC Architecture
 - 9.1.1 Distributed Coordination Function (DCF)
 - 9.1.2 Point coordination function (PCF)
 - 9.1.3 Coexistence of DCF and PCF
 - 9.1.4 Segmentation/Reorganization Summary
 - 9.1.5 MAC Data Service
 - 9.2 Distributed Coordination Function (DCF)
 - 9.2.1 Carrier Sense Mechanism
 - 9.2.2 MAC level confirmation
 - 9.2.3 Interframe Interval (IFS)
 - 9.2.4 Random Backoff Time
 - 9.2.5 DCF Access Procedure
 - 9.2.6 Transmission rules for directional MPDUs
 - 9.2.7 Transmission rules for broadcast and multicast MPDUs
 - 9.2.8 ACK procedure
 - 9.2.9 Detection and recovery of repetitive frames
 - 9.2.10 Timing of DCF
 - 9.3 PCF
 - 9.3.1 CFP Structure and Timing
 - 9.3.2 PCF access procedure
 - 9.3.3 PCF Transmission Procedure
 - 9.3.4 Non-competitive polling list
 - 9.4 Sub-paragraph
 - 9.5 Reorganization
 - 9.6 Multi-rate support
 - 9.7 frame exchange sequence
 - 9.8 MSDU transmission limit
- 10 layer management
 - 10.1 Overview of Management Models
 - 10.2 General management primitives

10.3 MLMESAP interface

10.3.1 Power Management

10.3.2 Scanning

10.3.3 Synchronization

10.3.4 Link Authentication

10.3.5 Unlocking Link Authentication

10.3.6 Associations

10.3.7 Reassociation

10.3.8 Disassociation

10.3.9 Reset

10.3.10 Startup

10.4 PLMESAP interface

10.4.1 PLME-RESET. request

10.4.2 PLME-CHARACTERISTICS. request

10.4.3 PLME-CHARACTERISTICS. confirm

10.4.4 PLME-DSSSTESTMODE. request

10.4.5 PLME-DSSSTESTOUTPUT. request

11 MAC Sublayer Management Entity

11.1 Synchronization

11.1.1 Basic method

11.1.2 Maintaining synchronization

11.1.3 Get Synchronization, Scan

11.1.4 Adjust STA timer

11.1.5 Frequency hopping (FH) Physical layer timing synchronization

11.2.1 Power management in the infrastructure network

11.2.2 Power Management in IBSS

11.3 Relevance and Reassignment

11.3.1 STA Association Procedure

11.3.2 AP Association Rules

11.3.3 STA reassociation procedure

11.3.4 AP reassociation procedure

11.4 Management Information Base (MIB) Definition

12 Physical Layer (PHY) Service Specification

12.1 Scope

12.2 PHY function