

ICS 29.130.10

CCS K 43



**NATIONAL STANDARD OF THE  
PEOPLE'S REPUBLIC OF CHINA**

**GB 1984-2014**

Replacing GB/T 1984-2014

---

**High-voltage alternating-current circuit-breakers**

高压交流断路器

**(English Translation)**

**Issued on: September 29, 2024**

**Implemented on: April 1, 2025**

---

**Issued by: State Administration for Market Regulation, China National  
Standardization Administration**

## Table of Contents

|                                                                             |
|-----------------------------------------------------------------------------|
| Preface                                                                     |
| 1 Scope                                                                     |
| 2 Normative references                                                      |
| 3 Terms and Definitions                                                     |
| 3.1 General Terms and Definitions                                           |
| 3.2 Final Assembly                                                          |
| 3.3 Assembly components                                                     |
| 3.4 Switchgear                                                              |
| 3.5 Components of a circuit breaker                                         |
| 3.6 Operational characteristics                                             |
| 3.7 Characteristic parameters                                               |
| 3.8 Fault Type                                                              |
| 4 Normal and special conditions of use                                      |
| 5 Rating                                                                    |
| 5.1 Overview                                                                |
| 5.2 Rated voltage ( $U_r$ )                                                 |
| 5.3 Rated insulation level ( $U_d$ , $U_p$ and $U_s$ )                      |
| 5.4 Rated frequency ( $f_r$ )                                               |
| 5.5 Rated continuous current ( $I_r$ )                                      |
| 5.6 Rated short-time withstand current ( $I_k$ )                            |
| 5.7 Rated peak withstand current ( $I_p$ )                                  |
| 5.8 Rated short circuit duration ( $t_k$ )                                  |
| 5.9 Rated supply voltage of auxiliary and control circuits ( $U_a$ )        |
| 5.10 Rated frequency of auxiliary and control circuit supply voltage        |
| 5.11 Rated pressure of compressed gas source for controlled pressure system |
| 5.12 Rated filling pressure/level for insulation and/or switching           |
| 5.101 Rated short-circuit breaking current ( $I_{sc}$ )                     |
| 5.102 Rated first open pole coefficient ( $k_{pp}$ )                        |
| 5.103 Rated short-circuit making current                                    |
| 5.104 Rated operating sequence                                              |
| 5.105 Rated out-of-step closing and breaking current                        |
| 5.106 Rated capacitive current                                              |

## 6 Design and structure

### 6.1 Requirements for liquid in circuit breakers

### 6.2 Requirements for gas in circuit breakers

### 6.3 Grounding of circuit breakers

### 6.4 Auxiliary and control equipment and circuits

### 6.5 Power Operation

### 6.6 Energy storage operation

### 6.7 Operation independent of non-locking (operation independent of manpower or power)

### 6.8 Human-operated actuators

### 6.9 Operation of the trip unit

### 6.10 Pressure/Liquid Level Indicator

### 6.11 Nameplate

### 6.12 Interlocking device

### 6.13 Position indication

### 6.14 Degree of protection of enclosure

### 6.15 Creepage distance of outdoor insulators

### 6.16 Gas and vacuum sealing

### 6.17 Liquid sealing

### 6.18 Fire (flammability)

### 6.19 Electromagnetic Compatibility (EMC)

### 6.20 X-ray emission

### 6.21 Corrosion

### 6.22 Insulation and/or switching, operating filling pressure/level

### 6.101 Requirements for inter-pole synchronization during single-close and single-break operations

### 6.102 General requirements for operation

### 6.103 Pressure limits of operating fluids

### 6.104 Exhaust hole

### 6.105 Time parameter

### 6.106 Mechanical load

### 6.107 Classification of circuit breakers

## 7 Type test

### 7.1 General Principles

### 7.2 Insulation test

### 7.3 Radio Interference Voltage Test (RIV)

- 7.4 Measurement of loop resistance
- 7.5 Continuous current test
- 7.6 Short-time withstand current and peak withstand current test
- 7.7 Protection level verification
- 7.8 Sealing test
- 7.9 Electromagnetic compatibility test (EMC)
- 7.10 Additional tests on auxiliary and control circuits
- 7.11 X-ray test of vacuum interrupter
- 7.101 Mechanical and environmental tests
- 7.102 Provisions for closing and opening tests
- 7.103 General principles for making and breaking tests
- 7.104 Explanation of arcing time
- 7.105 Short-circuit test parameters
- 7.106 Short circuit test procedure
- 7.107 Terminal fault test
- 7.108 Additional short-circuit test
- 7.109 Near-field fault test
- 7.110 Out-of-step closing and opening tests
- 7.111 Capacitive current test
- 7.112 Requirements for closing and opening tests of E2 class circuit breakers with rated voltage up to and including 40.5 kV
- 7.113 Noise level test
- 8 Factory Test
- 8.1 General Principles
- 8.2 Insulation test of main circuit
- 8.3 Testing of auxiliary and control circuits
- 8.4 Measurement of main circuit resistance
- 8.5 Sealing test
- 8.6 Design inspection and appearance inspection
- 8.101 Mechanical operation test
- 9 Guidelines for selection of circuit breakers
- 9.101 General
- 9.102 Selection of rated values under operating conditions
- 9.103 Selection of ratings under fault conditions
- 9.104 Selection of electrical life

- 9.105 Selection of capacitive load switching
- 10 Documents to be provided with enquiries, tenders and orders
  - 10.1 General
  - 10.2 Information provided with enquiries and orders
  - 10.3 Information provided with the tender documents
- 11 Rules for transportation, storage, installation, operation and maintenance
  - 11.1 General
  - 11.2 Conditions during transportation, storage and installation
  - 11.3 Installation
  - 11.4 Operation
  - 11.5 Maintenance
    - 11.101 Resistors and Capacitors
- 12 Safety
- 13 Impact of products on the environment
- Appendix A (Normative) Tolerances of test parameters during the test
- Appendix B (Normative) Type test records and reports
  - B.1 Data and results to be recorded
  - B.2 Contents of type test report
- Appendix C (Normative) Use of mechanical properties and related requirements
- Appendix D (Normative) Requirements for closing and opening test procedures for metal-enclosed circuit breakers and dead-shell circuit breakers
  - D.1 General
  - D.2 Reduced number of closing and breaking units for testing
  - D.3 Test of single pole in one enclosure
  - D.4 Test of three poles in one enclosure
- Appendix E (Normative) Requirements for circuit breakers with disconnecting resistors
  - E.1 General
  - E.2 Opening and closing performance verification
  - E.3 Resistor connection time
  - E.4 Current carrying performance
  - E.5 Insulation performance
  - E.6 Mechanical properties
  - E.7 Requirements for the technical specifications of disconnecting resistors
  - E.8 Example of recovery voltage waveform
- Appendix F (Normative) Method for determining expected TRV