

ICS 03.220.20; 93.080.30
CCS R 80



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB 21253-2007

Sign and marking of special lane for Olympic vehicles

奥林匹克专用车道标志和标线

(English Translation)

Issued on: November 1, 2007

Implemented on: January 1, 2008

Issued by: Standardization Administration of China

Table of Contents

- Foreword
- 1 Scope
- 2 Normative references
- 3 Terms and Definitions
- 4 Olympic lanes logo
- 5 Olympic lanes flag
- 6 Olympic lanes markings
- 7 Olympic lanes set of signs and markings
 - 7.1 Olympic lanes flag
 - 7.2 Olympic lanes markings
- 8 Olympic lanes and signs marking material

Foreword

All the technical contents of this standard is mandatory.

The standard proposed by the Beijing Traffic Management Bureau.

This standard by the National Traffic engineering facilities (highway) Standardization Technical Committee (SAC/TC223) centralized.

This standard is mainly drafted by. Ministry of Communications Highway Research Institute, the Beijing Traffic Management Bureau, National Transportation Safety Facilities Quality Supervision and Inspection Center, Beijing Hua Technology Co., Ltd. in the cross.

1 Scope

This standard specifies the general provisions of the Olympic lanes signs and markings.

This standard applies to signs and markings on the Olympic lanes during the 2008 Beijing Olympic Games.

2 Normative references

The following documents contain provisions which, through reference in this standard and become the standard terms. For dated references, subsequent Amendments (not including errata content) or revisions do not apply to this standard, however, encourage the parties to the agreement are based on research Whether the latest versions of these documents. For

undated reference documents, the latest versions apply to this standard.

GB 5768 traffic signs and road markings GB/T 8416 surface color visual signal GB/T 18833 road traffic signs reflective film JT/T 279 road traffic sign board JT/T 280 pavement marking paint JT/T 493 preformed road marking tape

3 Terms and Definitions

The following terms and definitions apply to this standard.

It refers to the 2008 Beijing Olympic Games period, the general vehicle services for the Olympic Games.

It refers to the 2008 Beijing Olympic Games period, in the competition and training venues, Olympic family members residence, the media hotels, airports, Between the Main Press Center, radio and television centers, and other venues and related facilities and services for the Olympic Games, the Olympic vehicular traffic and set Opposing lanes.

4 Olympic lanes logo

4.1

Olympic lanes are identified by white, color pattern composed of the Olympic rings. Olympic lanes for traffic signs and road Reticle surface, shown in Figure 1.

Color Range 4.2 Olympic lanes logo design in compliance with the GB/T 8416's.

Figure 1 identifies the Olympic lanes

5 Olympic lanes flag

5.1

Olympic lanes marked as directional signs, the background is blue.

5.2

Olympic lanes sign located above the lane, the flag may not be facing the lane when you can label right, or left arrow callout Arrow, shown in Figure 2. Flag dimensions shown in Figure 3.

Figure 2 Olympic lanes flag

3 Olympic lanes flag size 2

5.3

Olympic lanes flag indicates that the Olympic lanes reserved for vehicles with other vehicles and pedestrians allowed to enter.

6 Olympic lanes markings

6.1

Olympic lane markings by the Olympic lanes and lane identification ground composition, shown in Figure 4.

Central, road dimensions shown in Figure 6.2 identifies the Olympic lanes road identification provided Olympic lanes 5, according to the lane Width scaled appropriately.

6.3

Road direction side of the motor vehicle lanes as the Olympic lanes, one side of the roadway edge line (solid line) remains unchanged, Driveway on the other side of the dividing line dividing line using existing roadway facilities classified as yellow and white dotted line.

Intermediate motor vehicle lane road 6.4 direction as the Olympic lanes, the roadway on both sides of the dividing line between the use of existing roadways points Boundary areas designated for the yellow and white dotted line.

6.5

Olympic lanes markings indicating the lane reserved for Olympic vehicle, other vehicles and pedestrians allowed to enter.

4 Olympic lanes markings Book GB 21253-2007 Centimeters

5 Olympic lanes markings size

7.1 Olympic lanes flag

7.1.1

Olympic lanes flag, and the installation space required settings according to the relevant provisions of GB 5768.

7.1.2

mark set in place before entering the Olympic lanes starting point and each intersection entrance, located at the top of the indicated lane right Side or the left side.

7.2 Olympic lanes markings

7.2.1

Olympic road lanes should be applied designated Olympic lanes markings.

7.2.2

lane after a start and every once plotted intersection Olympic lanes identity. Intersection intervals as long distance (such as super Over 3km), also increased depending on the

circumstances identified in the appropriate locations.

8 Olympic lanes and signs marking material

Reflective film 8.1 Olympic lanes flag should be consistent with GB/T 18833 requirements, marking plate shall comply with the requirements of JT/T 279's Claim.

8.2

Olympic lanes marking paint shall comply with JT/T 280 requirements Olympic lanes
Marking preformed marking tape shall comply with JT/T 493 requirements.