

ICS 97.190
CCS Y57



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB 30004-2013

The safety requirements of cradles

婴儿摇篮的安全要求

Issued on: October 10, 2013

Implemented on: June 1, 2015

**Issued by: General Administration of Quality Supervision, Inspection and
Quarantine of the People's Republic of China;
Standardization Administration of China**

Table of Contents

- 1 Scope
- 2 Normative references
- 3 Terms and definitions

Foreword

All technical content of this standard is mandatory. This standard was drafted in accordance with the rules given in GB/T 1.1-2009. Please note that certain contents of this document may involve patents. The issuing agency of this document is not responsible for identifying these patents. This standard was proposed by the China National Light Industry Council. This standard is under the jurisdiction of the National Toy Standardization Technical Committee (SAC/TC253). Drafting organizations of this standard. Shanghai Institute of Quality Supervision and Inspection Technology, Zhongshan Longcheng Daily Products Co., Ltd., Ningbo Mommy Baoying Children's Products Manufacturing Co., Ltd., Shenzhen Huace Testing Co., Ltd., Guangdong Entry-Exit Inspection and Quarantine Bureau Inspection and Quarantine Technology Center Toy Experiment Office, Shantou City, Guangdong Province, Quality and Measurement Supervision and Testing Institute, Beijing China Light Industry Association Certification Center The main drafters of this standard. Chen Jingru, Zhang Ruohong, Chen Zhaoren, Zhou Jiapeng, Zhu Ping, Li Shili, Chen Sipao. Safety requirements for baby cradle

1 Scope

GB 30004-2013 is the Chinese national standard on the safety requirements of cradles, in the field of domestic and commercial equipment, entertainment, sport. It carries no /T suffix, which in the Chinese system means compliance is mandatory: a product or a practice within its scope has to meet it to be lawfully made, sold or carried out in China. It was issued on 10 October 2013 by the General Administration of Quality Supervision, Inspection and Quarantine of the People's Republic of China; Standardization Administration of China, and has been in force since 1 June 2015. Classification: ICS 97.190, CCS Y57. This page is published from the official record of the standard held by the Chinese standards administration: the identification, the dates, the classification and the issuing body are taken from there. The clause text, the tables and the numeric limits are in the document itself, which is delivered complete in English translation.

2 Normative references

The following documents are indispensable for the application of this document. For dated reference documents, only the dated version applies to this article. For undated references, the latest version (including all amendments) applies to this document.

GB/T 2912.1 Textiles Determination of Formaldehyde Part

GB/T 3920 Textile color fastness test color fastness to rubbing

GB/T 3922 Test method for color fastness to perspiration of textiles

GB/T 5713 Textile color fastness test color fastness to water GB 6675 Toy safety

GB/T 7573 Determination of pH value of textile water extract

GB/T 17592 Determination of prohibited azo dyes in textiles

GB 18401 National Basic Safety Technical Code for Textile Products

GB 18584 Limits of harmful substances in interior decoration materials and wooden furniture

GB/T 18886 Textile color fastness test color fastness to saliva

3 Terms and definitions

The following terms and definitions apply to this document.

3.1 Baby cradle cradles For babies less than 5 months old or babies who cannot sit up, kneel up, or climb up, the inner length of the bottom surface is not more than 900mm, A human-driven baby bed that can swing and balance itself. Usually there is a base with wheels, or a swingable base, or any structure that can swing relative to a fixed base.

3.2 Accesszone The reachable area of the baby cradle that cannot be penetrated from the side panels and end panels is the entire inner bottom surface of the cradle and the bottom surface. The area within 380mm. The reachable area of the baby cradle that can be penetrated by the hand from the side and end plates is the entire inner part of the cradle and the distance above the bottom surface is 380mm. The area within the cradle, as well as the arc of the radius within 380mm from the horizontal surface of the bottom surface, and within 150mm below the horizontal