

ICS 71.120
CCS G95



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB 46035-2025

Replacing GB 25432-2010

Rubber and plastics machinery - General safety requirements

橡胶塑料机械 通用安全要求

Issued on: August 1, 2025

Implemented on: August 1, 2026

**Issued by: State Administration for Market Regulation;
Standardization Administration of China**

Table of Contents

1 Scope	1
2 Normative references	1
3 Terms and Definitions	2
4 General safety requirements and/or protection or risk reduction measures	2
4.1 General Requirements	2
4.2 Ergonomics	3
4.3 Operating Position	3
4.4 Start, stop and restart functions	3
4.5 Emergency Stop	4
4.6 Protective devices	4
4.7 Electrosensitive protective equipment	5
4.8 Two-hand control device	5
4.9 Pressure-sensitive mats, floors, and edges	5
4.10 Power-operated guards	6
4.11 Safety-related components of control systems	6
4.12 Automatic Monitoring	6
4.13 Moving Parts	6
4.14 Hose	7
4.15 Electrical and Electromagnetic Interference	7
4.16 Overheated parts or materials	7
4.17 Noise	7
4.18 Gas, Fume and Dust	8
4.19 Slips, Trips and Falls	8
4.20 Hydraulic and pneumatic systems	8
5 Specific safety requirements for closed rubber mixing mills and plastic mixing mills	8
5.1 Safety protection against mechanical hazards in the charging area	8
5.2 Safety protection against mechanical hazards in the transition trough area of tandem internal mixers	9
5.3 Safety protection against mechanical hazards in the unloading area	10
5.4 Safety protection against mechanical hazards caused by movement of rotor drive elements	10
6 Specific safety requirements for open rubber and plastic mixing mills	10
6.2 Hazards due to reduced braking performance	10

6.3 Hazards of suction and crushing by roller drive mechanisms	10
6.4 Suction and crushing hazards between the rubber guard and the rollers	11
6.5 Additional safety requirements for emergency release of personnel	11
6.6 Specific requirements for large mixing mills ($D \geq 400$ mm)	11
6.7 Specific requirements for small mixing mills ($D \leq 200$ mm)	14
6.8 Specific requirements for medium-sized mixing mills ($200 \text{ mm} < D < 400 \text{ mm}$)	16
7 Specific safety requirements for rubber and plastic extruders	16
7.1 Drive and transmission device, screw shaft	16
7.2 Openings on the barrel	16
7.3 Hopper	16
7.4 Single/Double Roller Feeding System	16
7.5 Stuffing feeding system	17
7.6 Overvoltage Protection	17
7.7 Screen Changer	17
7.8 Melt gear pump	17
7.9 Exhaust system	17
7.10 Extruder head	17
7.11 Horizontal movement of power-operated machinery and its components	18
8 Specific safety requirements for die face pelletizers in rubber and plastic extrusion lines	18
8.1 Melt connector, start valve	18
8.2 Pelletizing area, pelletizing room	18
8.3 Granular material discharge area/reversing device, cooling and conveying medium outlet area	19
8.4 Drive motor and transmission area	19
8.5 Horizontal moving wheel set	19
8.6 Hazards due to loss of stability	19
9 Specific safety requirements for traction devices in rubber and plastic extrusion lines ...	19
9.1 Feeding area	19
9.2 Conveying area, driving and power transmission area	20
9.3 Discharging area	20
9.4 Falls due to gravity/uncontrolled descent	20
9.5 Additional requirements for full body access	20
9.6 Startup and machine setup operations in hazardous areas	21
10 Specific safety requirements for rubber and plastics calendaring machines	21
10.1 General Requirements	21

10.2 Preventing entry into the crushing area	22
10.3 Additional requirements for cleaning	23
10.4 Hazards caused by transmission systems	23
10.5 Hazards at the auxiliary rollers	24
10.6 Hazards caused by auxiliary equipment	24
10.7 Dynamic movement of engaging/disengaging calenders	25
11 Specific safety requirements for rubber and plastic injection molding machines	25
11.1 Hazards arising from mold closing movements in the mold area	25
11.2 Hazards arising from mold closing movements on the non-operating side of the mold area	26
11.3 Hazards caused by movements other than mold closing movements during production	26
11.4 Use of protective devices with control functions	28
11.5 Safety requirements for machines with descending templates	30
11.6 Additional requirements for machines where the entire body of the person is accessible between the mold area and the interlocked guard or light curtain	30
11.7 Additional requirements for machines where the entire human body enters the mold area	31
11.8 Clamping mechanism area or area behind the movable platen	32
11.9 Areas outside the mold area and/or the clamping mechanism where the ejector and ejector pins and their drive mechanisms move	33
11.10 Nozzle Area	33
11.11 Injection device area	34
11.12 Product drop area	34
12 Specific safety requirements for rubber and plastic blade crushers	35
12.1 Crushing chamber	35
12.2 Feeding area	35
12.3 Discharge area	36
13 Specific safety requirements for rubber and plastic strand pelletizers	36
13.1 Cutting Chamber	36
13.2 Feeding device	37
13.3 Feeding area	37
13.4 Discharge area	37
13.5 Starting device	37
13.6 Water spill hazard	37
14 Specific safety requirements for rubber and plastic shredders	37
14.1 Chopping chamber	37

14.2 Feeding area	38
14.3 Discharge Area	39
15 Specific safety requirements for plastic pelletizers	39
15.1 Granulation Chamber	39
15.2 Feeding of non-pre-cut materials	40
15.3 Moving parts of the discharge system	40
16 Specific safety requirements for flat vulcanizing presses	40
16.1 Mold Area	40
16.2 Clamping device area outside the mold area	43
16.3 Hazards of Power-Operated Die Clamping Systems	44
16.4 Dangers of Power-Operated Die Changing Devices	45
16.5 Full body access to the mold area, movable guard or light curtain and flat vulcanizing press	45
16.6 Flatbed vulcanizing press with full access to the mold area	46
16.7 Reciprocating/rotary plate vulcanizing press	47
17 Specific safety requirements for tire shaping and curing presses	47
17.1 Overview	47
17.2 Moving the upper part closed (closing movement) and open (opening movement) ...	48
17.3 Accidental fall of the mobile upper part at the mold opening limit position	48
17.4 Accidental fall of the mobile upper part at any position of the mold opening	49
17.5 Moving the upper locking device to lock or unlock	49
17.6 Lowering, raising, moving in and out of the tire loading device and/or tire storage device	49
17.7 Tire mounting device falls in raised position	49
17.8 Tire removal device movement	50
17.9 The movement of applying or releasing the clamping force, the movement of the automatic locking and unlocking device of the mold sleeve, the upward and downward movement of the movable mold operating device Downward movement	50
17.10 When the vulcanizing machine is above the semi-closed position (secondary shaping position), apply pressure of	50
17.12 Before the steam chamber is unlocked, the pressure in the steam chamber is too high	51
17.14 Before unlocking, the capsule pressure is too high	51
17.15 Bladder leakage causes hot water to accumulate between the bladder and the tire	51
17.17 Rear Inflator	51
18 Usage Information	52