

ICS 23.020.30

CCS J 74



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB 8335-2011

**[GB/T 8335-2011] Special threads for gas cylinders
(English Translation)**

Issued on: December 30, 2011

Implemented on: December 1, 2012

**Issued by: General Administration of Quality Supervision, Inspection and
Quarantine**

Table of Contents

Foreword...	3
1 Scope...	5
2 Normative references...	5
3 Terms and definitions, symbols...	5
4 Taper thread...	7
5 Cylindrical thread...	10

1 Scope

This Standard specifies the terms, symbols, basic profile and size of taper threads and cylindrical pipe threads for gas cylinders.

This Standard applies to the taper thread for connection of the opening of the gas cylinder to the cylinder valve, and the cylindrical pipe thread (hereinafter referred to as the cylindrical thread) for connection of the valve protection cap to the neck ring.

The taper thread for connection of fusible plug of the gas cylinder with safety device to plug seat can also refer to this Standard.

2 Normative references

The following documents are indispensable for the application of this document.

For dated references, only the dated version applies to this document. For undated references, the latest edition (including all amendments) applies to this document.

GB/T 192, General purpose metric screw threads - Basic profile

GB/T 196, General purpose metric screw threads - Basic dimensions

GB/T 197, General purpose metric screw threads - Tolerances

GB/T 3505, Geometrical Product Specifications (GPS) - Surface texture:

Profile method - Terms, definitions and surface texture parameters

GB/T 13005, Terminology of gas cylinders

3.1 Terms and definitions

Terms and definitions determined by GB/T 13005 and the following ones are applicable to this document.

3.1.1

Basic plane

The plane, of basic diameter, perpendicular to the thread axis, which is referred to as the base plane.

Note: For internal thread, it is the plane of the big end; for external thread, it is the plane whose distance to the small end is equal to the basic distance.

3.1.2

Basic diameter

The basic major diameter of the internal or external thread.

3.1.3

Taper thread pitch

The distance between the parallel cone generatrices of the corresponding two points of the neighboring teeth on the pitch diameter line.

3.1.4

Taper thread pitch diameter deviation

It refers to the comprehensive pitch diameter deviation, including the pitch diameter radial compensation value that is caused by the deviation of the pitch diameter itself and the profile half-angle deviation, screw-pitch deviation, and cone angle deviation.

3.1.5

Basic distance

The distance from the basic plane to the small end of the taper external thread, which is referred to as the base distance.

3.1.6

Reference plane

Small end face of external taper thread (visible plane for inspection), large end face of internal taper thread (visible plane for inspection).

3.2 Symbols

The following symbols apply to this document.

D(d) Major diameter of the internal (external) thread base surface;

D₂(d₂) Pitch diameter of the internal (external) thread base surface;

.....