



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB 8953-2018

**National food safety standard - Hygienic regulation for soy
sauce**

Issued on: June 21, 2018

Implemented on: December 21, 2019

**Issued by: National Health Commission and State Administration for
Market Regulation**

Table of Contents

Foreword	3
1 Scope	4
2 Terms and definitions	4
3 Selection of site and plant environment	4
4 Factory building and workshops	4
5 Facilities and equipment	6
6 Hygiene management	9
7 Raw-materials of food, food additives and food-related products	10
8 Food safety control in production process	11
9 Inspection	14
10 Storage and transport of products	14
11 Management of product recall	14
12 Training	14
13 Management systems and personnel	14
14 Recording and document management	14
Appendix A Guideline to microbiological monitoring procedures for processing of soy sauce	15

1 Scope

This standard specifies the basic requirements and management guidelines for the sites, facilities and personnel in the procurement, processing, packaging, storage and transport of raw-materials in the production process of soy sauce.

This standard applies to the production of soy sauce.

2 Terms and definitions

The terms and definitions as defined in GB 14881-2013 apply to this document.

3 Selection of site and plant environment

It shall comply with the relevant provisions of clause 3 of GB 14881-2013.

4.1.2 According to the needs of the production process of soy sauce, it may set

such working stages as raw-material processing, mold-starter propagation, brewing, spraying, blending, sterilization, filling and so on.

4.1.3 Each production workshop or internal area shall be divided into a cleaning

operation area (filling room), a quasi-cleaning operation area (mold-starter propagation, fermentation, spraying, blending, sterilization, etc.), a general working area (raw-material warehouse and finished product warehouse). The production workshop shall be provided with personnel channels and material transport channels, respectively.

4.2.1 General requirements

that needs to be kept dry.

5.1.5.3 Handwashing facilities shall contain dispensers for close-free cleaning

detergents and disinfectants, dryers or paper towels. For disinfection of hands, if a chlorine disinfectant is used, the concentration of free chlorine shall reach to 50 mg/kg.

5.1.5.4 The drainage of hand-washing facilities shall be directly connected to

the sewer pipe, where there is a device to prevent backflow, harmful animal intrusion, or odor.

5.1.5.5 If the toilet is set up in the locker room of the production workshop, the

door of the toilet shall not face the door of production workshop. There shall be a flushing device and pedal-type or inductive hand washing facilities in the toilet, as well as good ventilation and lighting facilities.

5.1.6.2 Brewing, packaging and storage places shall be well ventilated to

prevent excessive indoor temperature, steam condensation or odor. If necessary, it shall be equipped with the ventilation equipment.

5.1.6.3 The mold-starter propagation room shall have air-conditioning facilities.

5.1.6.4 Ventilation & exhaust devices shall be easy to disassemble for cleaning, repair or replacement, the vents shall have anti-corrosion mesh covers. The air inlet must be more than 2 m above the ground and away from sources of pollution and exhaust.

5.1.6.5 Exhaust equipment with sufficient capacity shall be installed in places

of steaming & boiling, mold-starter propagation, oil spraying.

5.1.6.6 The air inlet of mechanical ventilation shall be fitted with a corrosion-resistant open-close protective cover that is easy to clean and replace, and away from pollution sources and exhaust outlets.

5.1.7.2 If there is a light inspection facility in the filling process, it shall meet the lighting inspection conditions.

5.1.8.1 It shall comply with the relevant provisions of 5.1.8 of GB 14881-2013.

It shall comply with the relevant provisions of 5.2.2 of GB 14881-2013.

5.2.3.1 It shall comply with the relevant provisions of 5.2.3 of GB 14881-2013.

5.2.3.2 The water supply and drainage systems for the factory buildings, equipment, other mechanical facilities shall, under normal conditions, be subjected to the overall overhauling, maintenance, repair at least once a year.

6.1 Hygiene management system

It shall comply with the relevant provisions of 6.1 of GB 14881-2013.

6.2.3 The mold-starter propagation room and mold-starter seeding room shall be cleaned and disinfected regularly. It shall take measures to prevent the mold-starter seeding and the finished mold-starter from being contaminated by bacteria.

6.3 Health management and hygiene requirements for food processing personnel

6.3.1.1 It shall establish and implement the health management system for food processing personnel.

6.3.1.2 Food processing personnel shall be subjected to health checks every year and obtain health certificates. They shall receive hygiene training before going to their posts.

6.3.1.3 If the food processing personnel have diseases that are harmful to food safety as prescribed by relevant national laws and regulations, they shall be arranged to other posts that do not affect food safety.

7.2.4 The warehousing and use of raw-materials of food shall follow the

principle of "early-in, early-out". It shall be stored separately according to different batches of raw-materials of food. Pay attention to avoid moisture and mildew during storage, perform regular or irregular inspections, remove the raw-materials which have signs of deterioration and mildew in time.

7.2.5 If there are special storage conditions for the raw-materials of food, the

storage conditions shall be controlled and recorded.

7.2.6 Qualified raw-materials of food and unqualified raw-materials of food shall

be stored separately. They shall be marked clearly to distinguish them.

7.3 Food additives

It shall comply with the provisions of 7.3 of GB 14881-2013.

7.4 Food-related products and others

It shall comply with the provisions of 7.4 and 7.5 of GB 14881-2013.

8.1.2 It is encouraged to use the Hazard Analysis and Critical Control Point

Systems (HACCP) to control the key control points (such as temperature, time, pressure, disinfection concentration, etc.) in the processing of soy sauce.

8.1.3 When it finds abnormality in the production monitoring, it shall find the

causes quickly, make corrections in time, take records.

8.1.4 All products shall be stored under the conditions the comply with the

relevant production operation regulations or relevant standards. It shall take effective measures to prevent secondary contamination during production or storage.

8.1.5 Equipment, containers and tools which are used for conveying, loading

and storing raw-materials, semi-finished products and finished products shall be operated, used and maintained to avoid contamination of products during processing or storage.

8.2.1.1 It shall comply with the provisions of 8.2 of GB 14881-2013.

After the mold-starter is released, clean the mold-starter propagation pool and floor to keep it clean. Disinfect it if necessary.