

ICS 83.080.01

CCS G 32



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 11547-2008

**Plastic -- Methods of test for the determination of the effects of
immersion in liquid chemicals**

塑料 耐液体化学试剂性能的测定

(English Translation)

Issued on: September 4, 2008

Implemented on: April 1, 2009

**Issued by: General Administration of Quality Supervision, Inspection and
Quarantine of PRC**

Table of Contents

Foreword	3
1 Scope	5
2 Normative references	5
3 Principle	6
4 General technical requirements and procedures	7
5 Determination of mass, size, appearance change	11
6 Test of changes of other physical properties	21
7 Test report	23
2008	24
Appendix B (Normative) Type of test solution that achieve status conditioning equilibrium	28
References	29

1 Scope

1.1

This standard specifies the measurement of the performance change of plastic specimen as immersed in liquid chemical reagent without being affected by external influences. This standard does not include the environmental stress cracking test (ESC) as specified in ISO 22088-2:2006, ISO 22088-3:2006, ISO 22088-4:2006.

1.2

This standard only applies to the determination of the specimen the surface of which is completely immersed in liquid chemical reagents.

Note: This method may not be suitable for partial immersion or intermittent immersion of plastic specimens.

1.3

This standard applies to all solid plastics, such as molded or extruded plastics, sheets, tubes, rods or sheets which have a thickness of more than 0.1 mm. This standard does not apply to porous plastic materials.

2 Normative references

The provisions in following documents become the provisions of this standard through reference in this standard. For the dated references, the subsequent amendments (excluding corrections) or revisions do not apply to this standard;

however, parties who reach an agreement based on this standard are encouraged to study if the latest versions of these documents are applicable.

For undated references, the latest edition of the referenced document applies.

GB/T 1034-2008 Plastics - Determination of water absorption (ISO 62:2008, IDT)

GB/T 1690-2006 Rubber vulcanized or thermoplastic - Determination of the effect of liquids (ISO 1817:2005, MOD)

GB 2536-1990 Transformer oils (neq IEC 60296:1982)

GB/T 2918-1998 Plastics - Standard atmospheres for conditioning and testing (idt ISO 291:1997)

GB/T 8806-1988 Measurement method of dimensions of plastic pipes (eqv ISO 3126: 1974)

GB/T 15596-1995 Plastics - Determination of changes in color and variations in properties after exposure to daylight under glass, natural weathering or artificial light (eqv ISO 458: 1980)

GB/T 17037.3-2003 Plastics - Injection moulding of test specimens of thermoplastic materials - Part 3: Small plates (ISO 294 3:2002, IDT)

ISO 2818:1994 Plastics - Preparation of test specimens by machining

ISO 3205:1976 Preferred test temperature

3 Principle

Under the conditions of specified temperature and specified time, soak the specimen completely into the test solution.

Before and after soaking, respectively determine the performance of specimen.

If possible, it may also be determined after drying. In the latter case, in the same group of specimens, carry out test one by one as much as possible.

Note: Only when the specimens used have the same shape, the same size (especially the same thickness) and very similar conditions (internal stress, surface, etc.), this test method can compare

the performance between different plastics.

The prescribed test methods are as follows:

- a) Immediately after soaking or post-soaking drying, determine the change in mass, size and appearance of the specimen;
- b) Immediately after soaking or post-soaking drying, determine the change of physical properties of the specimen (mechanical properties, thermal properties, optical properties, etc.);
- c) Liquid absorption volume.

If it is required to determine that the material is still affected by the liquid, it shall use the method of testing immediately after soaking. If it is required to determine the status of the material under the effect of liquid (the liquid is volatile), it shall use the method of testing after post-soaking drying. This method can determine the effect of soluble components.

Chinese Standards

This is an excerpt of the PDF (Some pages are marked off intentionally)

Full-copy PDF can be purchased from 1 of 2 websites:

nu SEARCH the standard ID, such as GB 4943.1-2022.

nu Select your country (currency), for example: USA (USD); Germany (Euro).

nu Full-copy of PDF (text-editable, true-PDF) can be downloaded in 9 seconds.

nu Tax invoice can be downloaded in 9 seconds.

nu Receiving emails in 9 seconds (with download links).

nu SEARCH the standard ID, such as GB 4943.1-2022.

nu Full-copy of PDF (text-editable, true-PDF) can be downloaded in 9 seconds.

nu Receiving emails in 9 seconds (with PDFs attached, invoice and download links).

Translated by: Field Test Asia Pte. Ltd. (Incorporated & taxed in Singapore. Tax ID: 201302277C)

Linkin: <https://www.linkedin.com/in/waynezhengwenrui/>

----- The End -----