

ICS 33.160.50

CCS M 72



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 12060.21-2025

**Sound system equipment - Part 21: Acoustical
(output-based) measurements
(English Translation)**

Issued on: May 30, 2025

Implemented on: December 1, 2025

**Issued by: State Administration for Market Regulation, China National
Standardization Administration**

Table of Contents

Preface	
Introduction	
1 Scope	
2 Normative references	
3 Terms, definitions and abbreviations	
3.1 Terms and Definitions	
3.2 Abbreviations	
4 Type Description	
5 Physical properties	
5.1 Terminal and controller markings	
5.2 Size	
5.3 Quality	
5.4 Connectors and cable assemblies	
6 Design Data	
7 Condition	
7.1 Rating conditions	
7.2 Climate conditions	
7.3 Normal measurement conditions	
8 Test signal	
8.1 Overview	
8.2 Sine frequency sweep signal	
8.3 Steady-state single-frequency signal	
8.4 Steady-state dual-frequency signal	
8.5 Sparse Multi-frequency Polyphonic Signals	
8.6 Broadband Noise Signal	
8.7 Narrowband Noise Signal	
8.8 Hann Burst Signal	
8.9 Pulse signal	
9 Acoustic Environment	
9.1 General	
9.2 Free field conditions	
9.3 Half-space free-field condition	

- 9.4 Simulating free-field conditions
- 9.5 Half-space simulation of free-field conditions
- 9.6 Diffuse Field Conditions
- 9.7 Target application conditions
- 10 Positioning of DUT
 - 10.1 Rated geometric conditions
 - 10.2 Measurement distance between microphone and DUT
- 11 Measurement equipment and test results
- 12 Accuracy of acoustic measurements
 - 12.1 General
 - 12.2 Measurement uncertainty
- 13 DUT Installation
 - 13.1 Driver Installation and Acoustic Loading
 - 13.2 Installation of electroacoustic system and acoustic load
- 14 Preprocessing
- 15 Rated environmental conditions
 - 15.1 Temperature range
 - 15.2 Humidity range
- 16 Rated frequency range
- 17 Input signal
 - 17.1 Rated maximum input value
 - 17.2 Maximum input level
- 18 Sound pressure output
 - 18.1 Rated maximum sound pressure
 - 18.2 Rated maximum sound pressure level
 - 18.3 Short-term maximum sound pressure level
 - 18.4 Long-term maximum sound pressure level
 - 18.5 Sound pressure in a specified frequency band
 - 18.6 Sound pressure level in a specified frequency band
 - 18.7 Average sound pressure in a specified frequency band
 - 18.8 Average sound pressure level in the specified frequency band
- 19 Frequency response of fundamental frequency component
 - 19.1 Transfer Function
 - 19.2 Sound Pressure Level Frequency Response
 - 19.3 Time-varying amplitude compression of fundamental frequency components

- 19.4 Maximum Input Amplitude Compression
- 19.5 Correction based on free-field reference measurement
- 19.6 Effective Frequency Range
- 19.7 Internal Delay
- 20 Directional characteristics
 - 20.1 Overview
 - 20.2 Direct Sound Field in 3D Space
 - 20.3 Directivity Far Field Characteristics
 - 20.4 Output sound power
 - 20.5 Sound power level
 - 20.6 Average sound output power in the frequency band
 - 20.7 Radiation angle
 - 20.8 Coverage angle
 - 20.9 Average sound pressure level in the acoustic area
- 21 Harmonic Distortion
 - 21.1 Overview
 - 21.2 Nth-order harmonic component
 - 21.3 Total Harmonic Components
 - 21.4 Total Harmonic Distortion
 - 21.5 Higher-order harmonic distortion
 - 21.6 Maximum sound pressure level limited by total harmonic distortion
 - 21.7 Nth Order Equivalent Input Harmonic Distortion Component
 - 21.8 Equivalent Input Total Harmonic Distortion
- 22 Intermodulation distortion under dual frequency excitation
 - 22.1 Changes in Excitation Frequency
 - 22.2 Intermodulation Distortion
 - 22.3 Amplitude Modulation Distortion
- 23 Multi-tone distortion
 - 23.1 Required conditions
 - 23.2 Measurement methods
- 24 Pulse distortion
 - 24.1 Pulse Distortion Level
 - 24.2 Maximum pulse distortion ratio
 - 24.3 Average Pulse Distortion Level
 - 24.4 Crest Factor of Pulse Distortion

25 Stray magnetic field

25.1 Overview

25.2 Static components

25.3 Dynamic components

Appendix A (Informative) Uncertainty Analysis

Appendix B (Normative) Transducer Installation

B.1 Standard baffle

B.2 Standard measurement box

Appendix C (Normative) Analog Program Signal

Appendix D (Informative) Evaluation of maximum input and output values

Appendix E (Informative) Spherical Wave Expansion

E.1 Spherical wave expansion coefficient

E.2 Directivity coefficient

E.3 Directivity factor

E.4 Output sound power

Appendix F (Informative) Nonlinearity

F.1 Equivalent input harmonic distortion

F.2 Dual-frequency intermodulation

F.3 Signal distortion generated in audio systems

Appendix G (Informative) Stray Magnetic Field

References

Foreword

This document is in accordance with the provisions of GB/T 1.1-2020 "Guidelines for standardization work Part 1: Structure and drafting rules for standardization documents" Drafting.

This document is part 21 of GB/T 12060 "Sound system equipment". GB/T 12060 has published the following parts.

- Part 1: Overview;
- Part 2: Interpretation of general terms and calculation methods;
- Part 3: Audio amplifier measurement methods;
- Part 4: Microphone measurement methods;
- Part 5: Test methods for main performance of loudspeakers;