

ICS 33.060.20

CCS M 36



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 12192-2017

**Methods of measurement for transmitters employing F3E or
G3E emissions used in the mobile services**

(English Translation)

Issued on: December 29, 2017

Implemented on: July 1, 2018

**Issued by: General Administration of Quality Supervision, Inspection and
Quarantine of the People's Republic of China, Standardization
Administration of the People's Republic of China**

Table of Contents

Foreword	
1 Scope	
2 Normative references	
3 Terms and Definitions, Abbreviations	
3.1 Terms and Definitions	
3.2 Abbreviations	
4 Standard Test Condition	
4.1 Working Conditions	
4.2 Standard conditions for basic power supply	
4.3 Standard atmospheric conditions	
4.4 Standard day working cycle condition	
5 Supplementary test conditions	
5.1 Transmitter Input Signal Configuration, Modulation Limits, and Pre-emphasis	
5.2 Output Signal Measurement Configuration for Transmitters with Antenna Ports Connected	
5.3 Output Signal Measurement Configuration for a Transmitter with a Monolithic Antenna	
5.4 Audio Band Limits	
5.5 Tested Device Interface Condition	
5.6 Radiation Measurement Condition	
6 Requirements for measuring equipment	
7 Frequency error	
7.1 Overview	
7.2 Measurement Method	
8 Output carrier power	
8.1 Overview	
8.2 Measurement Method	
9 Radiated carrier power	
9.1 Average radiation carrier power	
9.2 Maximum Effective Radiated Carrier Power	
10 Scattering frequency components	
10.1 Overview	
10.2 Measurement method for transmitters with antenna ports	

10.3	Measurement method for a transmitter with a self-contained antenna
11	Spurious noise
11.1	Overview
11.2	Measurement Methods for Transmitters with Connected Antenna Ports
11.3	Measurement Method for Transmitters with Monolithic Antennas
12	Adjacent channel power
12.1	Overview
12.2	Measurement Methods Using a Power Measuring Receiver
12.3	Measurement Methods Using Non-Digitally Stored Spectrum Analyzers
12.4	Measurement Methods Using Digitally Stored Spectrum Analyzers
13	Input Power and Total Efficiency
13.1	Input Power
13.2	Overall efficiency
14	Intermodulation conversion loss between transmitters (TIMCL)
14.1	Overview
14.2	Measurement method for transmitters with antenna ports connected
14.3	Measurement method for a transmitter with a self-contained antenna
15	Modulation Characteristics
15.1	Overview
15.2	Measurement Method
15.3	Expression of results
16	Modulation sensitivity
16.1	Overview
16.2	Measurement Method
17	Total distortion factor
17.1	The total distortion coefficient of an audio sine wave
17.2	The Total Distortion Factor of Two Audio Sine Waves
18	Relative audio intermodulation product level
18.1	Overview
18.2	Measurement Method
18.3	Results Representation
19	Compressor Characteristics
19.1	Compressor Total Amplitude Characteristics
19.2	Compressor Startup and Recovery Time
20	Modulation limit

20.1 Overview

20.2 Measurement Method

20.3 Result Expression

21 Remaining modulation

21.1 Remaining FM

21.2 Remaining AM

22 Transmitter startup time

22.1 Overview

22.2 Transmitter carrier startup time

22.3 Transmitter frequency conversion time

Appendix A (Normative) Test Site Usage Guide

A.1 Overview

A.2 Open Field (OATS)

A.3 Low Reflectance Test Site (LRTS)

A.4 Anechoic Chamber (AC)

Appendix B (Normative Appendix) Recommended Features of Measuring Equipment

B.1 Frequency Deviation and Modulation Depth Measurers

B.2 True RMS Voltage Table

B.3 distortion factor and SINAD meter

B.4 frequency measuring instrument

B.5 Audio band limiting filter

B.6 Standard Test Receiver

B.7 Power Measurement Receiver

B.8 Spectrum Analyzer

Appendix C (Informative Appendix) Example of Transmission Line Impedance Stabilization Network

C.1 Introduction

C.2 Measurement method of interference voltage

Figure 1 Measurement configuration for input signal

Figure 2 Output signal configuration with a self-contained antenna transmitter relative measurement

Figure 3 Measurement configuration of a stray frequency component of a transmitter with an antenna port connected

Figure 4 Measurement configuration with spurious noise connected to antenna port transmitters (using test receiver)

Figure 5 Measurement configuration with spurious noise connected to antenna port transmitters (using a spectrum analyzer)

- Figure 6 Measurement configuration of spurious noise with a fully-armed antenna transmitter (using a test receiver)
- Figure 7 Measurement configuration of spurious noise with monolithic antenna transmitters (using a spectrum analyzer)
- Figure 8 Measurement of adjacent channel power configuration (using a power measurement receiver)
- Figure 9 Measurement of adjacent channel power configuration (using a spectrum analyzer)
- Figure 10 Measurement configuration of intermodulation conversion loss between transmitters with connected antenna ports (using circulators and transmission line extenders)
- Figure 11 Measurement configuration of intermodulation conversion loss between transmitters with connected antenna ports (using resistive or capacitive couplers)
- Figure 12 Measurement configuration of intermodulation conversion loss between transmitters with self-contained antennas (using circulators and transmission line extenders)
- Figure 13 Measurement configuration of intermodulation conversion loss between transmitters with self-contained antennas (using resistive or capacitive couplers)
- Figure 14 Measurement configuration for modulation characteristics
- Figure 15 Measurement configuration for relative audio intermodulation product levels
- Figure 16 Measurement configuration for compressor characteristics
- Figure 17 Measurement setup for transmitter start-up time
- Figure A.1 Measurement configuration for open field RF emissions
- Figure A.2 Measurement configuration for open field RF reception
- Figure A.3 3m site size 38 in the grid
- Figure A.4 LRTS RF emission measurement configuration using radio wave absorbers
- Figure A.5 LRTS RF Receive Measurement Configuration Using Radio Wave Absorbers
- Figure A.6 Ground reflected wave suppression
- Figure A.7 Higher position to reduce ground reflections
- Figure A.8 Example of anechoic chamber
- Figure C.1 Transmission line impedance stabilization network (also called simulated transmission network)
- Figure C.2 Interference voltage vector diagram
- Figure C.3 Example of transmission line impedance stabilization network
- Table 1 Voltage of Each Cell
- Table 2 Standard Test Voltages for Different Operating Currents
- Table 3 Standard atmospheric conditions for arbitration test
- Table 4 Channel spacing and specified bandwidth and their respective frequency increments Δf