

ICS 75.1
CCS E 30



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 12583-1998

Replacing GB/T 12583-1990

**Standard test method for measurement of extreme-pressure
properties of lubricating fluids (four-ball method)**

(English Translation)

Issued on: December 8, 1998

Implemented on: May 1, 1999

Issued by: State Quality and Technical Supervision

Table of Contents

What this standard covers	1
Document data	2

What this standard covers

This standard specifies the method for the determination of lubricant extreme pressure properties, do the following three tests. Load - Wear Index LWI. Sintering the point P (D). Maximum nonseizure load P (B). This standard applies to lubricants. This standard relates to certain hazardous materials, operations and equipment, but has no intention of all the security issues related to this proposal are made??. Therefore, the user before using this standard to establish appropriate safety and health practices and determine the applicability of the management system. This standard uses the legal units of measurement, given the illegal practice of using fixed units of measurement in parentheses.

Document data

International classification (ICS): 75.1.

Chinese classification (CCS): E30.

Estimated length of the Chinese original: 10,153 words.

Adopted international standard: ASTM D2783-1988 (1993), MOD.

Supersedes the earlier edition GB/T 12583-1990.