

CCS K 15



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 13542.2-2021

Plastic films for electrical purposes - Part 2: Methods of test

Issued on: October 11, 2021

Implemented on: May 1, 2022

**Issued by: State Administration for Market Regulation, China National
Standardization Administration**

Table of Contents

1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 General description of the test	2
4.1 Sampling	2
4.2 Pretreatment conditions	2
4.3 Test condition	2
5 thickness	2
5.1 Overview	2
5.2 Mechanical Law	3
5.2.1 Overview	3
5.2.2 Single layer method	3
5.2.2.1 Principle	3
5.2.2.2 Measuring instrument	3
5.2.2.3 Measurement	3
5.2.2.4 Results	3
5.2.3 Stacking method	3
5.2.3.1 Measuring instrument	3
5.2.3.2 Measurement	3
5.2.3.3 Results	3
5.3 Gravimetric method (mass density method)	4
5.3.1 Determine the average thickness of the sample by gravimetric method	4
5.3.1.1 Principle	4
5.3.1.2 Measuring instrument	4
5.3.1.3 Measurement	4
5.3.1.4 Results	4
5.3.2 Determine the average thickness of rolls by gravimetric method	4
5.4 Lateral thickness distribution and longitudinal thickness variation	4
6 Density	4
7 width	4
8 Windability (offset/curved or recessed)	5
8.1 Principle	5

8.2 Overview	6
8.3 Method A	6
8.3.1 Principle	6
8.3.2 Offset/arc measurement	6
8.3.2.1 Equipment	6
8.3.2.2 Sample	7
8.3.2.3 Procedure	7
8.3.2.4 Results	7
8.3.3 Measurement of depression	7
8.3.3.1 Equipment	7
8.3.3.2 Sample	7
8.3.3.3 Procedure	7
8.3.3.4 Results	8
8.4 Method B	8
8.4.1 Principle	8
8.4.2 Equipment	8
8.4.3 Sample	8
8.4.4 Procedure	8
8.4.5 Results	9
9 Surface roughness	9
9.1 Overview	9
9.2 Measuring principle	9
9.3 Test equipment and supplies	9
9.4 Sample	9
9.5 Procedure	9
9.6 Results	9
10 Porosity	9
10.1 Test equipment	9
10.2 Sample	9
10.3 Procedure	10
10.4 Results	10
11 Coefficient of friction	10
12 Wetting tension (polyolefin film)	10
12.1 Principle	10
12.2 Equipment	10

12.3 Reagent	10
12.4 Sample	11
12.5 Condition processing	11
12.6 Procedure	12
12.7 Evaluation	12
12.8 Results	12
13 Tensile strength and elongation at break	12
13.1 Overview	12
13.2 Sample	12
13.3 Test speed	12
13.4 Procedure	12
13.5 Test results	13
14 Edge tearing	13
14.1 Overview	13
14.2 Sample	13
14.3 Procedure	13
14.4 Test results	14
15 Internal tear	14
16 Stiffness	14
17 Surface resistivity	14
18 Volume resistivity	14
18.1 Method 1 Electrode method	14
18.2 Method 2 Model capacitor method (applicable to winding capacitor dielectric films or thinner films for method 1)	15
18.2.1 Principle	15
18.2.2 Sample	15
18.2.3 Equipment or appliances	16
18.2.4 Procedure	16
18.2.5 Results	16
19 Dielectric dissipation factor and permittivity	16
19.1 Overview	16
19.2 Method 1 Contact electrode method	16
19.2.1 Overview	16
19.2.2 Sample and specimen handling	16
19.2.3 Sample condition processing before measurement	16

19.2.4 Contact electrode measurement	17
19.2.4.1 Overview	17
19.2.4.2 Electrode material	18
19.2.4.2.1 Evaporating or vacuum spraying metal	18
19.2.4.2.2 Conductive silver paint	18
19.2.4.2.3 Metal foil	18
19.3 Method 2 Non-contact electrode measurement	18
19.3.1 Overview	18
19.3.2 Air substitution method	18
19.3.2.1 Variable pitch method	18
19.3.2.1.1 Principle	18
19.3.2.1.2 Electrode structure	19
19.3.2.1.3 Measuring the bridge	19
19.3.2.1.4 Sample	19
19.3.2.1.5 Procedure	19
19.3.2.1.6 Results	20
19.3.2.2 Variable capacitance method	20
19.3.2.2.1 Principle	20
19.3.2.2.2 Electrode structure	20
19.3.2.2.3 Measuring the bridge	20
19.3.2.2.4 Sample	20
19.3.2.2.5 Procedure	20
19.3.2.2.6 Results	21
19.3.3 Fluid discharge method	21
19.4 Method 3 Model capacitor method	21
19.4.1 Overview	21
19.4.2 Equipment	21
19.4.3 Sample	22
19.4.4 Procedure	22
19.4.5 Test results	22
20 Dielectric loss factor in the immersed state	23
21 Electric strength	23
21.1 AC and DC test (sheet-like film sandwiched between metal electrodes)	23
21.2 DC test (model capacitor element)	23
21.2.1 Test device	23