

ICS 29.120.60

CCS K 30



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 14048.15-2006

**Low-voltage switchgear and controlgear -- Part 5-6: Control
circuit devices and switching elements -- DC interface for
proximity sensors and switching amplifiers (NAMUR)**

低压开关设备和控制设备 第5-6部分：控制电路电器和开关元件-接近传感器和开
关放大器的DC接口（NAMUR）

(English Translation)

Issued on: September 14, 2006

Implemented on: April 1, 2007

**Issued by: General Administration of Quality Supervision, Inspection and
Quarantine of the People's Republic of China, Standardization
Administration of the People's Republic of China**

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard applies to two-wire connection cable is connected to the control input terminal switching amplifiers action proximity sensor. The switching amplifier to the control circuit includes a DC power supply, and by the close control of the sensor resistance change. If the electrical special co GB 3835. 4-2000 standard, they can also be used in an explosive atmosphere.

Document data

International classification (ICS): 29.120.60.

Chinese classification (CCS): K30.

Estimated length of the Chinese original: 12,128 words.

Adopted international standard: IEC 60947-5-6-1999, IDT.

Standards quoted by this document

GB 3836.4-2000; GB 14048.1-2006; GB/T 14048.10-1999; IEC 60947-5-2: 1999