

ICS 83.060

CCS G 40



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 1693-2007

Replacing GB/T 1693-1981 (1989); GB/T 1694-1981

**Vulcanized rubber -- Determination of dielectric constant and
dielectric loss angular tangent value**

硫化橡胶 介电常数和介质损耗角正切值的测定方法

(English Translation)

Issued on: May 14, 2007

Implemented on: October 1, 2007

**Issued by: General Administration of Quality Supervision, Inspection and
Quarantine of the People's Republic of China, Standardization
Administration of the People's Republic of China**

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard applies to vulcanized rubber. Warning: The use of this standard laboratory personnel should experience regular work. This standard does not indicate that all possible safety problems. Users are responsible for taking appropriate safety and health practices and to ensure compliance with the relevant conditions of the national regulations. This standard specifies two methods for determining the dielectric constant and dielectric loss tangent values. A determination method (50 Hz) frequency is lower. A method for the determination of the high-frequency electric field.

Document data

International classification (ICS): 83.060.

Chinese classification (CCS): G40.

Estimated length of the Chinese original: 16,195 words.

Supersedes the earlier edition GB/T 1693-1981 (1989); GB/T 1694-1981.

Standards quoted by this document

GB/T 2941