

ICS 53.100
CCS P 97



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 16937.1-1997

Replacing GB/T 16937-2010

**Earth-moving machinery--Operator's field of view--Test
method and performance criteria
(English Translation)**

Issued on: July 21, 2020

Implemented on: November 1, 2020

Issued by: State Administration for Market Regulation

Table of Contents

Preface
Introduction
1 Scope
2 Normative references
3 Terms and definitions
4 Basic size
5 Test equipment and facilities
6 Test configuration of the machine
7 Performance criteria for visual aids
8 Test procedure
9 Calculation method
10 Evaluation methods and performance criteria
11 Test report
12 Visibility information of the driver's manual
Appendix A (informative appendix) Dimensions and positions of HH and RR
References

Foreword

This standard was drafted in accordance with the rules given in GB/T 1.1-2009.

This standard replaces GB/T 16937-2010 "Earth-moving machinery driver visual field test methods and performance criteria". This standard and Compared with GB/T 16937-2010, the main technical changes except for editorial changes are as follows.

---Modified the normative reference documents, replacing the corresponding Chinese documents with international documents (see Chapter 2, Chapter 2 of the 2010 edition);

---Modified some terms and definitions (see 3.5, 3.6 and 3.9, 3.5, 3.6 and 3.9 in the 2010 edition);

---Added the auxiliary visual field requirements and the location of the display device (see 7.1 and 7.2);

---Modified the requirements of the performance criteria of the reflector (see 7.3, 7.1 of the 2010 edition);

---Added the provision of using auxiliary devices to meet relevant standards for shadow

measurement (see 8.3.1);

---Modified the performance criteria for the visibility of the 1m bounding rectangle (see 10.2, 10.2 in the 2010 edition);

---Modified the requirements for large, derived and other types of earth-moving machinery not included in the standard (see 10.4, 10.4 in the 2010 edition);

---Added the content related to visual field assistance in the detailed report of the machine (see 11.1);

---Added the cleaning of visual aids in the driver's manual (see Chapter 12);

---Added the position size used in the graphical test of "backhoe loader-side shift" and "skid steer loader" (see Appendix A).

The translation method used in this standard is equivalent to ISO 5006:2017 "Earth-moving machinery driver visual field test methods and performance criteria".

The Chinese documents that have consistent correspondence with the normatively cited international documents in this standard are as follows.

---GB/T 6572 earthmoving machinery hydraulic excavator terms and commercial specifications (GB/T 6572-2014, ISO 7135:2009, IDT)

---GB/T 8420 The body size of the earth-moving machinery driver and the minimum activity space of the driver (GB/T 8420-2011, ISO 3411:2007, IDT)

---GB/T 8498 basic type identification, terms and definitions of earth-moving machinery (GB/T 8498-2017, ISO 6165:2012, IDT)

---GB/T 8591 Earth-moving machinery driver seat calibration point (GB/T 8591-2000, eqvISO 5353.1995)

---GB/T 21154 Earth-moving machinery and the quality measurement method of its working devices and parts (GB/T 21154-2014, ISO 6016:2008, IDT)

---GB/T 32070 Earth-moving machinery hazard monitoring system and its visual auxiliary device performance requirements and tests (GB/T 32070-2015, ISO 16001:2008, IDT) this standard was proposed by China Machinery Industry Federation.

This standard is under the jurisdiction of the National Earth-moving Machinery Standardization Technical Committee (SAC/TC334).

Drafting organizations of this standard. Tianjin Engineering Machinery Research Institute Co., Ltd., Lonking (Shanghai) Machinery Manufacturing Co., Ltd., Xuzhou Xugong Excavator Machinery Co., Ltd., Qingdao Lovol Construction Machinery Co., Ltd., Shaanxi Tongli Heavy Industry Co., Ltd., Inner Mongolia North Heavy Vehicle Co., Ltd.

Company, Lingong Group Jinan Heavy Machinery Co., Ltd.

Introduction

The purpose of this standard is to use objective engineering terms that can be quantified to express the visibility around the machine that the driver can see.

The driver can operate the machine correctly, effectively and safely. This standard includes a test method using two lights located in the eyes of the driver. By machine the shadow caused by the device and its components and accessories is determined on the minimum rectangular boundary line and the visibility test circle with a distance of 1m around the machine.

Fixed. The radius of the test circle is 12m. The method used does not capture the full position of the driver's visibility, but provides information to help determine Acceptable performance of machine visibility. The guidelines in this standard provide designers with guidance on acceptable visibility shading areas.

According to the visibility of the driver and the operation mode of the machine, the test method divides the area around the machine into six areas. front (zone A), front side Face (Zone B and C), back side (Zone D and E) and back (Zone F).

For each area, the physical characteristics of the driver are taken into consideration. Except for 65mm eye distance (50% of the driver's normal binocular distance), Considering that the driver may turn the head and move the upper body left and right, additional eye distance adjustment is added. So for area A, area B and area C, the eye distance the range is expanded to 405mm. For Zone D, Zone E and Zone F, the driver's head rotation and upper body rotation are determined by the body shape of the seated driver.

limited. Therefore, for zone D, zone E and zone F, the maximum reachable eye distance is 205mm. For some machine types, follow the driver's Ergonomics, the eye distance used is less than the maximum allowable value. This is done to keep the machine at the current state of the art.

The 300mm shadow size on the bounding rectangle represents the approximate thickness of the chest of the person working on the approach area of the earthmoving machinery (see 2D "chest thickness" in ISO 3411).

The performance criteria for visibility are based on the body shape of human drivers and ground personnel using various representative sizes, as well as Provide machine design that meets visibility requirements. In order to formulate visibility criteria, a combination of eye position and shadow width is used. In each There is an appropriate position between the shadows, which can meet the requirements when there are multiple shadows in the area.

In situations where direct vision is deemed insufficient, indirect visibility auxiliary devices (reflectors or closed circuit television (CCTV)) can be used to achieve Acceptable visual

performance. For the bounding rectangle (RB), it is better to use a supplementary indirect view device (reflector or CCTV). Other auxiliary equipment Set (see ISO 16001) can be used in special cases.

On-site organization can be an effective form of supplementation to compensate for the remaining visibility shading.

Earthmoving machinery driver's vision Test methods and performance criteria

1 Scope

This standard specifies the boundary rectangle and 12m visibility test circle (VTC) used to determine and evaluate driver visibility around the machine the static test method.

This standard applies to earth-moving machinery that is defined by ISO 6165 and that travels on construction sites and on highways and has a seated driver position. this According to the type of machine family in Table 1, the standard specifies the performance criteria for the visibility of various machines that reach the maximum work quality of ISO 6165.

For machines not listed, including large machines, derived earth-moving machinery and other types of earth-moving machinery, the visibility test procedure can be refer to the implementation and use it in conjunction with the risk assessment procedures defined in 10.4.

2 Normative references

The following documents are indispensable for the application of this document. For dated reference documents, only the dated version applies to this article Pieces. For undated references, the latest version (including all amendments) applies to this document.

ISO 3411 Earth-moving machinery driver's body size and the driver's minimum movement space
(Earth-movingmachinery-Physicaldimensionsofoperatorsandminimumoperatorspaceenvelope)
ISO 5353 Earth-moving machinery driver seat calibration point (Earth-moving machinery, andtractors and machinery for agricultureandforestry-Seatindexpoint)
ISO 6016 The quality measurement method of earth-moving machinery and its working devices and components
(Earth-movingmachinery-Methodsofmeasuringthemasessofwholmachines,theirequipment andcomponents)
ISO 6165 Earth-moving machinery basic type identification, terms and definitions (Earth-movingmachinery-Basictypes-Identificationandtermsanddefinitions)
ISO 7135 Terminology and Commercial Specifications for Earth-moving Machinery Hydraulic Excavators
(Earth-movingmachinery-Hydraulicexca-vators-Terminologyandcommercialspecifications)
ISO 16001 Earth-moving machinery hazard monitoring system and its visual auxiliary