

ICS 23.060.01

CCS N 16



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 17213.3-2005

**Industrial-process control valves -- Part 3-1: Dimensions -- Face-to-face
dimensions for flanged, two-way, globe-type, straight pattern and center-to-face
dimensions for flanged, two-way, globe-type, angle pattern control valves**

工业过程控制阀 第3-1部分：尺寸 两通球形直通控制阀法兰端面距和两通球形角
形控制阀法兰中心至法兰端面的间距

(English Translation)

Issued on: September 9, 2005

Implemented on: April 1, 2006

**Issued by: General Administration of Quality Supervision, Inspection and
Quarantine of the People Republic of China, China National
Standardization Administration Committee**

Table of Contents

What this standard covers	1
Document data	2

What this standard covers

This standard specifies a certain nominal diameter and pressure rating of the two-pass ball through the control valve from the end face (FTF) and angular control valve center to the flange face flange spacing (CTF). Through the control valve nominal diameter of DN 15 ~ DN 400, angle control valve nominal diameter of DN 25 ~ DN 400.

Document data

International classification (ICS): 23.060.01.

Chinese classification (CCS): N16.

Estimated length of the Chinese original: 8,856 words.

Adopted international standard: IEC 60534-3-1-2000, IDT.