

ICS 29.060.20

CCS K13



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 19216.1-2021

**Circuit integrity test for electric cables or optical fiber cables under fire conditions - Part
1: Test method for fire with shock at a temperature of at least 830 °C for cables of rated
voltage up to and including 0.6/1 kV and with an overall diameter exceeding 20 mm**

在火焰条件下电缆或光缆的线路完整性试验 第1部分：火焰温度不低于830 °C的
供火并施加冲击振动，额定电压0.6/1 kV及以下外径超过20 mm电缆的试验方法

(English Translation)

Issued on: May 21, 2021

Implemented on: December 1, 2021

**Issued by: State Administration for Market Regulation, China National
Standardization Administration**

Table of Contents

1	Scope
2	Normative references
3	Terms and definitions
4	Test environment
5	Test equipment
6	Samples (power cables and control cables with rated voltage 0.6/1kV and below)
7	Test procedure (power cable and control cable with rated voltage 0.6/1kV and below)
9	Repeat the test procedure
10	Test report (power cable and control cable with rated voltage 0.6/1kV and below)
11	Cable mark
1	Scope
2	Normative references
3	Terms and definitions
3.1	Circuit integrity
3.2	Draught-free environment
4	Test environment
5	Test equipment
5.1	Test device
5.3.3	Verification of the heat source
5.4	Shock and vibration generating device
5.5	Location of the heat source
5.7	Fuse
6	Samples (power cables and control cables with rated voltage 0.6/1kV and below)
6.1	Sample preparation
6.2	Installation of the sample
6.2.1	Multi-core cables and single-core cables with concentric metal layers
7.3	Supplying fire and applying shock and vibration
7.4	Applied voltage
8.1	Fire time
8.2	Eligibility criteria
9	Repeat the test procedure
10	Test report (power cable and control cable with rated voltage 0.6/1kV and below)

What is delivered

The English PDF of this standard, delivered to your email address.

Instant delivery: the file is sent automatically after payment.