

ICS 25.040.40; 35.240.50
CCS N 10



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 21099.5-2024

**Devices and integration in enterprise systems - Function
blocks(FB) for process control and electronic device
description language(EDDL) - Part 5: EDDL Built-in library
(English Translation)**

Issued on: November 28, 2024

Implemented on: June 1, 2025

**Issued by: State Administration for Market Regulation, China National
Standardization Administration**

Table of Contents

Preface	
Introduction	
1 Scope	
2 Normative references	
3 Terms, definitions, abbreviations and abbreviations	
3.1 Terms and Definitions	
3.2 Abbreviations and abbreviations	
4 Conventions for built-in descriptions	
5 Built-in categories	
5.1 Overview	
5.2 User interface built-in	
5.3 Communication built-in	18
5.4 Action built-in	
6 EDDL built-in library	
6.1 General Principles	25
6.2 User Interface Built-in	
6.2.1 Built-in ACKNOWLEDGE	
6.2.2 Built-in acknowledgement	
6.2.3 Built-in Delay	
6.2.4 Built-in delay	
6.2.5 Built-in delayfor	
6.2.6 Built-in delayfor 2	
6.2.7 Built-in DISPLAY	
6.2.8 Built-in display	
6.2.9 Built-in display_bitenum	
6.2.10 Built-in display_builtin_error	
6.2.11 Built-in display_com_error	
6.2.12 Built-in display_comm_status	
6.2.13 Built-in display_device_status	
6.2.14 Built-in display_dynamics	
6.2.15 Built-in display_dynamics 2	
6.2.16 Built-in display_message	

- 6.2.17 Built-in display_message 2
- 6.2.18 Built-in display_response_code
- 6.2.19 Built-in display_response_status
- 6.2.20 Built-in display_xmtr_status
- 6.2.21 Built-in edit_device_value
- 6.2.22 Built-in edit_device_value 2
- 6.2.23 Built-in edit_local_value
- 6.2.24 Built-in edit_local_value 2
- 6.2.25 Built-in get_acknowledgement
- 6.2.26 Built-in get_acknowledgement 2
- 6.2.27 Built-in GET_DEV_VAR_VALUE
- 6.2.28 Built-in get_dev_var_value
- 6.2.29 Built-in GET_LOCAL_VAR_VALUE
- 6.2.30 Built-in get_local_var_value
- 6.2.31 Built-in Menu
- 6.2.32 Built-in MenuDisplay (Version A)
- 6.2.33 Built-in MenuDisplay (Version B)
- 6.2.34 Built-in PUT_MESSAGE
- 6.2.35 Built-in put_message
- 6.2.36 Built-in SELECT_FROM_LIST
- 6.2.37 Built-in select_from_list
- 6.2.38 Built-in select_from_menu
- 6.2.39 Built-in select_from_menu 2
- 6.2.40 Prompt string format
- 6.3 Communication built-in
 - 6.3.1 Built-in abort_on_all_comm_errors
 - 6.3.2 Built-in ABORT_ON_ALL_COMM_STATUS
 - 6.3.3 Built-in ABORT_ON_ALL_DEVICE_STATUS
 - 6.3.4 Built-in ABORT_ON_ALL_RESPONSE_CODES
 - 6.3.5 Built-in abort_on_all_response_codes
 - 6.3.6 Built-in ABORT_ON_COMM_ERROR
 - 6.3.7 Built-in abort_on_comm_error
 - 6.3.8 Built-in ABORT_ON_COMM_STATUS
 - 6.3.9 Built-in ABORT_ON_DEVICE_STATUS
 - 6.3.10 Built-in ABORT_ON_NO_DEVICE (deprecated)

- 6.3.11 Built-in ABORT_ON_RESPONSE_CODE
- 6.3.12 Built-in abort_on_response_code
- 6.3.13 Built-in ext_send_command
- 6.3.14 Built-in ext_send_command_trans
- 6.3.15 Built-in fail_on_al_comm_errors
- 6.3.16 Built-in fail_on_al_response_codes
- 6.3.17 Built-in fail_on_comm_error
- 6.3.18 Built-in fail_on_response_code
- 6.3.19 Built-in get_more_status
- 6.3.20 Built-in IGNORE_ALL_COMM_STATUS
- 6.3.21 Built-in IGNORE_ALL_DEVICE_STATUS
- 6.3.22 Built-in IGNORE_ALL_RESPONSE_CODES
- 6.3.23 Built-in IGNORE_COMM_ERROR
- 6.3.24 Built-in IGNORE_COMM_STATUS
- 6.3.25 Built-in IGNORE_DEVICE_STATUS
- 6.3.26 Built-in IGNORE_NO_DEVICE (deprecated)
- 6.3.27 Built-in IGNORE_RESPONSE_CODE
- 6.3.28 Built-in read_value
- 6.3.29 Built-in read_value 2
- 6.3.30 Built-in ReadCommand
- 6.3.31 Built-in retry_on_al_comm_errors
- 6.3.32 Built-in RETRY_ON_ALL_COMM_STATUS
- 6.3.33 Built-in RETRY_ON_ALL_DEVICE_STATUS
- 6.3.34 Built-in RETRY_ON_ALL_RESPONSE_CODES
- 6.3.35 Built-in retry_on_al_response_codes
- 6.3.36 Built-in RETRY_ON_COMM_ERROR
- 6.3.37 Built-in retry_on_comm_error
- 6.3.38 Built-in RETRY_ON_COMM_STATUS
- 6.3.39 Built-in RETRY_ON_DEVICE_STATUS
- 6.3.40 Built-in RETRY_ON_NO_DEVICE (deprecated)
- 6.3.41 Built-in RETRY_ON_RESPONSE_CODE
- 6.3.42 Built-in retry_on_response_code
- 6.3.43 Built-in send
- 6.3.44 Built-in send_al_values
- 6.3.45 Built-in send_command

- 6.3.46 Built-in send_command_trans
- 6.3.47 Built-in send_trans
- 6.3.48 Built-in send_value
- 6.3.49 Built-in send_value 2
- 6.3.50 Built-in SET_NUMBER_OF_RETRIES
- 6.3.51 Built-in WriteCommand
- 6.3.52 Built-in XMTR_ABORT_ON_ALL_COMM_STATUS
- 6.3.53 Built-in XMTR_ABORT_ON_ALL_DATA
- 6.3.54 Built-in XMTR_ABORT_ON_ALL_DEVICE_STATUS
- 6.3.55 Built-in XMTR_ABORT_ON_ALL_RESPONSE_CODES
- 6.3.56 Built-in XMTR_ABORT_ON_COMM_ERROR
- 6.3.57 Built-in XMTR_ABORT_ON_COMM_STATUS
- 6.3.58 Built-in XMTR_ABORT_ON_DATA
- 6.3.59 Built-in XMTR_ABORT_ON_DEVICE_STATUS
- 6.3.60 Built-in XMTR_ABORT_ON_NO_DEVICE (deprecated)
- 6.3.61 Built-in XMTR_ABORT_ON_RESPONSE_CODE
- 6.3.62 Built-in XMTR_IGNORE_ALL_COMM_STATUS
- 6.3.63 Built-in XMTR_IGNORE_ALL_DATA
- 6.3.64 Built-in XMTR_IGNORE_ALL_DEVICE_STATUS
- 6.3.65 Built-in XMTR_IGNORE_ALL_RESPONSE_CODES
- 6.3.66 Built-in XMTR_IGNORE_COMM_ERROR
- 6.3.67 Built-in XMTR_IGNORE_COMM_STATUS
- 6.3.68 Built-in XMTR_IGNORE_DATA
- 6.3.69 Built-in XMTR_IGNORE_DEVICE_STATUS
- 6.3.70 Built-in XMTR_IGNORE_NO_DEVICE (deprecated)
- 6.3.71 Built-in XMTR_IGNORE_RESPONSE_CODE
- 6.3.72 Built-in XMTR_RETRY_ON_ALL_COMM_STATUS
- 6.3.73 Built-in XMTR_RETRY_ON_ALL_DATA
- 6.3.74 Built-in XMTR_RETRY_ON_ALL_DEVICE_STATUS
- 6.3.75 Built-in XMTR_RETRY_ON_ALL_RESPONSE_CODES
- 6.3.76 Built-in XMTR_RETRY_ON_COMM_ERROR
- 6.3.77 Built-in XMTR_RETRY_ON_COMM_STATUS
- 6.3.78 Built-in XMTR_RETRY_ON_DATA
- 6.3.79 Built-in XMTR_RETRY_ON_DEVICE_STATUS
- 6.3.80 Built-in XMTR_RETRY_ON_NO_DEVICE (deprecated)