

ICS 91.120.40
CCS M 04



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 21714.2-2026

Replacing GB/T 21714.2-2015

Protection against lightning - Part 2: Risk management

雷电防护 第2部分：风险管理

(English Translation)

Issued on: July 30, 2026

Implemented on: February 1, 2027

Issued by: State Administration for Market Regulation

Table of Contents

Preface	
Introduction	
1 Scope	
2 Normative References	
3 Terms and Definitions	
4 Symbols	
5 Damage and Loss	
6 Risks and Risk Components	
8 Risk Component Assessment	
9 Frequency and Components of Damage	
Appendix A (Informative) Estimation of the Annual Average Number of Hazardous Events (NX)	
Appendix B (Informative) Estimation of Probability of Damage (PX)	
Appendix C (Informative) Estimation of Various Loss Rates (LX) in Buildings	
Appendix D (Informative) Estimation of PSPD	
Appendix E (Informative) Detailed Analysis of Additional Loss Rates (LE) Related to the Surrounding Environment	
Appendix F (Informative) Example 63 of Building Assessment	
References	

1 Scope 1

2 Normative References	1
3 Terms and Definitions	2
4 symbols	8
5 Damage and Loss	11
6 Risks and Risk Components	12
8 Risk Component Assessment	17

9 Frequency and Components of Damage 21

Appendix A (Informative) Estimation of the Annual Average Number of Hazardous Events (NX)	25
Appendix B (Informative) Estimation of Probability of Damage (PX)	33

Appendix C (Informative) Estimation of Various Loss Rates (LX) in Buildings 45

Appendix D (Informative) Estimation of PSPD 48

Appendix E (Informative) Detailed Analysis of Additional Loss Rates (LE) Related to the Surrounding Environment 60

Appendix F (Informative) Example 63 of Building Assessment

References 87

Figure 1. Flowchart for determining protection requirements and selecting protection measures to ensure $R \leq R_T$.

Figure 2. Example 20 of risk zoning

Figure 3. Flowchart for determining protection requirements and selecting protection measures to ensure $F \leq F_T$. 23

Figure A.1 Equivalent lightning interception area (AD) of an isolated building 26

Figure A.2 Buildings with complex shapes 27

Figure A.3 Determining the cut-off area of a given building using different methods 27

Figure A.4 Calculation of the cut-off area (AD) of a portion of a building 28

Figure A.5 Equivalent interception area (AD, ADJ, AM, AL, and AI) 32

Figure D.1 Discharge probability of the first return stroke for positive and negative polarities 49

Figure D.2 The probability P_{Up} corresponding to the 1kA residual voltage U_p' of the SPD is 51

Figure D.4 The probability P_{Up} corresponding to the 1kA residual voltage U_p' of SPD2 is 52

Figure D.5 The probability P_{Up} corresponding to the 1kA residual voltage U_p' of SPD2 is 53

Figure D.6 shows the probability P_{Up} corresponding to the 1kA residual voltage U_p' .

Figure D.7 Probability P_{Up} corresponding to the internal circuit length 54

Figure D.8 Probability P_{Up} corresponding to the internal circuit length 55

Figure D.9 The probability P_{Up} corresponding to the 1kA residual voltage U_p' of SPD2 is 56.

Figure D.10 shows the probability P_{Up} corresponding to the area of the internal loop when $n'=2$ and $w=0.1m$.

Figure D.11 shows the probability P_{Up} corresponding to the internal loop area when $n'=2$ and $w=0.5m$.

Figure D.12 shows the probability P_{Up} corresponding to the internal loop area when $n'=2$ and $w=0.1m$.

Figure D.13 Probability P_{Up} corresponding to the 1kA residual voltage U_p' of the SPD under different internal loop areas.

Figure D.14 Probability P_{Up} corresponding to different internal loop areas under two typical protection levels of GDT 59

Table 1.Comparison of Damage Sources, Causes, Loss Types, and Risk Components for Different Lightning Strike Points (Table 13)

Table 2 Factors Affecting Risk Components 14

Table 3 lists the risk components by source of damage and type of loss.

Table 4.Frequency components of various damage sources 22

Table A.1 Location factors CD and CDJ of buildings 29

Table A.2 Line Installation Factor (CI) 30

Table A.3 Line Type Factor (CT) 31

Table A.4 Line Environmental Factor (CE) 33

Table B.2 Reduction Factors (r_t) Related to Soil or Floor Surface Type 34

Table B.3 PLPS values related to direct lightning strike protection and physical damage reduction measures in exposed areas of buildings 35

Table B.4 Probability of Dangerous Sparks Caused by Lightning Strike on Buildings (PS) 36

Table B.5 Reduction Factors (r_p) Related to Fire Prevention Measures 36

Table B.6 Reduction Factor (r_f) Related to Building Fire or Explosion Risk 36

Table B.7 Typical PSPD values for SPDs used to protect against damage sources S1, S2, S3, and S4 in low-voltage systems (37)

Table B.8 Typical PSPD values of SPDs used to protect against damage sources S1, S2, S3, and S4 in communication systems 38

Table B.9 CLD and CLI values related to shielding, grounding, and isolation conditions 39

Table B.10 KS3 values related to internal wiring type 41

Table B.11 PLD values related to the resistance (RS) of the cable shield per unit length and the rated impulse withstand voltage (UW) of the equipment 42

Table B.12 PLD values related to the resistance (RS) of the cable shield per unit length and the higher equipment rated impulse withstand voltage (UW) 42

Table B.13 Typical PEB values corresponding to the Lightning Protection Level (LPL) of the SPD designed to withstand damage source S3.42

Table C.1 Loss rate values for each partition 45

Table C.2 Typical average values of LT, LD, LF1, LF2, LO1, and LO2 46

Table D.1 PUp value of voltage-limited SPD in the combination of voltage-limited SPD and voltage-switching SPD 52

Table D.2 PUp values of voltage-limited SPDs 55

Table E.1 Risk Components for Different Damage Sources and Loss Types (Applicable to Damage to the Surrounding Environment) 60

Table E.2 Loss Type L1. Typical Recommended Values for Personnel On-Site Time (tzE/8760) in Different Environments (Applicable to those specified in Table E.2)

(Environment type) 61

Table E.4 Loss Type L2. Typical Average Values of LF2E and LO2E Outside Buildings 62

Table F.1 Residential Buildings. Environmental and Building Characteristics 63

Table F.2 Residential Buildings. Power Supply Line 64

Table F.3 Residential. Communication Line 64

Table F.4 Residential Buildings. Equivalent Cut-off Area of Buildings and Lines 65

Table F.5 Residential. Expected average annual number of hazardous events 65

Table F.6 Residential Buildings. Risk Components of Personnel Stay Time and Risk Zoning 66

Table F.7 Residential. Z2 Zone (Building Interior) Value 66

Table F.8 Residential Buildings. Risk of Unprotected Structures (Value x 10⁻⁵) 67

Table F.9 Residential Buildings. Risk Components of Protected Buildings (Value x 10⁻⁵) 68

Table F.10 Office Buildings. Environmental and Building Characteristics 68

Table F.11 Office Building. Power Supply Line 69

Table F.12 Office Building. Communication Line 69

Table F.13 Office Buildings. Equivalent intercepted area of buildings and lines 70

Table F.14 Office Buildings. Estimated Average Annual Number of Hazardous Events 70

Table F.15 Office Building. Personnel Stay Time and Risk Components of Risk Zones 71

Table F.16 Office Building. Value 71 applicable to Zone Z1 (outside the entrance area)