

ICS 29.160.30

CCS K26



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 21967-2020

Replacing GB/T 21967-2008

**YBZE and YBZSE series flameproof electromagnetic braking
three-phase induction motors for crane application - Technical
specification**

YBZE、YBZSE系列起重用隔爆型电磁制动三相异步电动机 技术条件

Issued on: November 19, 2020

Implemented on: June 1, 2021

**Issued by: State Administration for Market Regulation;
Standardization Administration of China**

Table of Contents

1 Scope	1
2 Normative references	1
3 Type, basic parameters and dimensions	2
4 Technical requirements	8
5 Test method	11
6 Inspection rules	12
16 Appendix B (Normative Appendix) Determination of Braking Time	17

Foreword

This standard was drafted in accordance with the rules given in GB/T 1.1-2009. This standard replaces GB/T 21967-2008 "YBZE, YBZSE series of explosion-proof electromagnetic brake three-phase asynchronous motor technology for lifting Conditions", compared with GB/T 21967-2008, the main technical changes are as follows:

---Added references to GB/T 756, GB/T 1958, GB/T 1971, GB/T 22719.1, GB/T 22719.2, GB/T 21975, Deleted GB/T 13306-1991, JB/T 9615.1-2000, JB/T 9615.2-2000, JB/T 56105-1999 (see Chapter 2, Chapter 2 of the.2008 edition);

---Added motor model and example description (see 3.1);

--- The rated static braking torque in Table 2 is deleted, and its value is determined according to the technical agreement between the two parties (see Table 2 in the.2008 edition);

---Modified the D1 size of table 3, table 4, table 5 of frame size 180L (see table 3~table 5, table 3~table 5 of.2008 edition);

---Modified the K basic size and position tolerance of table 3 for frame numbers 160M~225M, and table 4 for frame numbers 112M~225M S basic size and position tolerance, table 5 S basic size and position tolerance of frame size 112M~250M (see table 3~ Table 5, Table 3~Table 5 of the.2008 edition);

--- Modify the key width tolerance of the shaft extension key in Table 6 (see Table 6, Table 6 of the.2008 edition);

---The requirement for the maximum surface temperature of the motor housing has been increased (see 4.10);

---Added "The deviation of any one phase of the DC resistance of the motor three-phase

stator winding in the actual cold state from the three-phase average value should not exceed $\pm 2\%$ of the average value. "(See 4.11);

---Added "At 40°C ambient temperature, the cold insulation resistance value of the motor stator winding should not be less than 5M Ω ." (see 4.12);

--- Added "1s test can also be used instead, but the test voltage value should be 120% of the specified value." (see 4.14);

---Modified the requirements of the alternating damp heat test (see 4.18, 4.17 of the.2008 edition);

--- Deleted the regulations on the unevenness of the air gap of the motor, and correspondingly canceled the inspection of the unevenness of the air gap (see.2008 edition 4.18);

1 Scope

GB/T 21967-2020 is the Chinese national standard on ybze and ybzse series flameproof electromagnetic braking three-phase induction motors for crane application - technical specification, in the field of electrical engineering. The /T suffix marks it as a recommended standard: it is not compulsory by itself, but it becomes binding as soon as a contract, a tender or a customer specification calls it up - which in practice is how most foreign buyers meet it. It was issued on 19 November 2020 by the State Administration for Market Regulation; Standardization Administration of China, and has been in force since 1 June 2021. Classification: ICS 29.160.30, CCS K26. This page is published from the official record of the standard held by the Chinese standards administration: the identification, the dates, the classification and the issuing body are taken from there. The clause text, the tables and the numeric limits are in the document itself, which is delivered complete in English translation.

This standard specifies the type, basic parameters and dimensions of YBZE and YBZSE series of explosion-proof electromagnetic brake three-phase asynchronous motors for lifting Dimensions, technical requirements, test methods, inspection rules, signs, packaging and warranty period. This standard is applicable to explosion-proof electromagnetic brake three-phase asynchronous motors (frame size 112~250) (below Referred to as "motor"), all series of motors derived from this series of motors can be implemented by reference.

2 Normative references

The following documents are indispensable for the application of this document. For dated reference documents, only the dated version applies to this article Pieces. For undated references, the latest version (including all amendments) applies to this document.

GB/T 191 Packaging, Storage and Transportation Graphic Mark

GB/T 755 Rotating motor rating and performance

GB/T 756 Cylindrical shaft extension of rotating motor

GB/T 757 Conical shaft extension of rotating electric machine

GB/T 997 Classification of structure type, installation type and junction box position of rotating electric machine (IM code)

GB/T 1032 Three-phase asynchronous motor test method

GB/T 1096 Ordinary flat key

GB/T 1958 Product Geometric Technical Specification (GPS) Geometric Tolerance Testing and Verification

GB/T 1971 Rotating motor wire end marking and direction of rotation

GB/T 1993 Rotating electric machine cooling method

GB/T 2423.4 Environmental testing of electrical and electronic products Part

3 Noise limit

GB/T 12351 Environmental technical requirements for tropical rotating electrical machines

GB 20294 Safety requirements for explosion-proof crane metallurgy and shielded motors

GB/T 21975 Three-phase asynchronous motor reliability test method for lifting and metallurgy

GB/T 22719.1 Inter-turn insulation of scattered windings of AC low-voltage motors Part