

ICS 17.040.30
CCS N 50



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 22183-2008

Test sieves for cereals

谷物检验筛

(English Translation)

Issued on: July 16, 2008

Implemented on: November 1, 2008

Issued by: Standardization Administration of China

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard specifies the requirements for grain test sieve. Grain Inspection sieve used in the laboratory for the detection of impurities in the grain sample and test sieve through the following specifications of the material. a) long hole test sieve b) test sieve hole in a) above are listed in the test sieve is mainly used for long hole from rye, triticale, durum wheat, common wheat and barley isolated " shrunken grain. " This does not include aperture 1. 50 mm and 1. 60 mm test sieve, sieve these two tests commonly used rice grading. While not including aperture 2. 50 mm and 2. 80 mm test sieve, sieve these two tests are usually used to test the malted barley. The hole diameter 1. 40 mm sieve is used to separate the rice debris. Diameter 1. 80 mm round hole sieve for sorghum. Diameter 4. 50 mm round hole sieve for separating broken grains from maize.

Document data

International classification (ICS): 17.040.30.

Chinese classification (CCS): N50.

Estimated length of the Chinese original: 9,932 words.

Adopted international standard: ISO 5223-1995, IDT.

Standards quoted by this document

ISO 2395-1990; ISO 3310-2-1990