

ICS 91.140.90
CCS Q 78



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 24474-2009

Replacing GB/T 24474-2009

**Measurement of ride quality - Part 1: Lifts (elevators)
(English Translation)**

Issued on: July 21, 2020

Implemented on: February 1, 2021

Issued by: State Administration for Market Regulation

Table of Contents

Foreword	
Introduction	
1 Scope	
2 Normative references	
3 Terms and definitions	
4 Measuring instruments	
4.1 General	
4.2 Features	
4.3 Vibration data processing	
4.4 Environmental impact	
4.5 Sound measurement requirements	
4.6 Calibration requirements	
5 Evaluation of transportation quality	
5.1 Calculation limit	
5.2 Acceleration and deceleration	
5.3 Jerk	
5.4 Vibration	
5.5 Speed	
5.6 Sound	
6 Expression of measurement procedures and results	
6.1 Preparation of measurement and presentation of results	
6.2 Location of the sensor	
6.3 Personnel	
6.4 Measurement procedure	
6.5 Reporting of results	
Appendix A (Normative Appendix) Calculation of Peak-to-Peak Vibration	
Appendix B (Normative Appendix) Calculation of constant acceleration and variable acceleration area	
Reference	

Foreword

GB/T 24474 "Measurement of Passenger Transport Quality" is divided into the following two parts.

---Part 1: Elevator;

---Part 2: Escalators and moving walks.

This part is Part 1 of GB/T 24474.

This section was drafted in accordance with the rules given in GB/T 1.1-2009.

This part replaces GB/T 24474-2009 "Elevator Ride Quality Measurement". Compared with GB/T 24474-2009, except for editorial changes in addition, the main technical content changes are as follows.

---Updated normative reference documents (see Chapter 2, Chapter 2 of the 2009 edition);

--- Deleted the definition of sound in the term (see 3.10 in the 2009 edition);

---Modified the definition of sound pressure level in terms (see 3.10, 3.11 of the 2009 edition);

---Modified the standards cited for the characteristics of measuring instruments (see Table 1, Table 1 of the 2009 edition);

---Added the provisions that should be noted in the test report under the presence of external sound sources (see 6.1.1).

This section uses the redrafting method to modify and adopt ISO 18738-1:2012 "Ride Quality Measurement Part 1: Elevator".

The technical differences between this part and ISO 18738-1:2012 and the reasons are as follows.

---Regarding normative reference documents, this section has made adjustments with technical differences to adapt to my country's technical conditions and adjustments.

The situation is collectively reflected in Chapter 2 "Normative Reference Documents", and the specific adjustments are as follows.

- Replace ISO 2041 with GB/T 2298, which is equivalent to the international standard (see Chapter 3);

- Replace IEC 61672-1 (see Chapter 3, Table 1, 4.5) with GB/T 3785.1 equivalent to the international standard;

- Replace IEC 61672-2 (see Chapter 3, 4.6.4) with GB/T 3785.2 equivalent to the international standard;

- Replace ISO 5805 with GB/T 15619, which is equivalent to adopting international standards (see Chapter 3);
- Replace ISO 8041 with GB/T 23716 equivalent to the international standard (see Table 1, 4.3.1, 4.3.2, 4.4, 4.6.2, 4.6.3);
- Replace ISO/IEC Guide98-3 (see 6.5) with GB/T 27418 which is modified to adopt international standards.
- The definition of the term 3.10 "sound pressure level" has been modified so that Part 1 and Part 2 of this series of standards are harmonized.

This section has made the following editorial changes.

- Deleted the content in the introduction that is not suitable for my country's national conditions, because its existence does not affect the use of this section;
- Added the statement of applicability of this part in Chapter 1 "Scope";
- In the 3.11 equivalent sound pressure level, "Fast" is changed to "F (Fast)" to be consistent with GB/T 3785.1-2010;
- In Table 1, the "Fast" in the "Time Weighting" column of the "Sound" column is changed to "F (Fast)" in order to be consistent with GB/T 3785.1-2010 to; modify the unit symbol "dB(A)" to "dB" to meet the relevant requirements of GB/T 3102.7-1993;
- Added the sub-clause numbers of 4.3 and 6.5 for easy application;
- In the references, the corresponding international standards are replaced by national standards for ease of application.

This part is proposed and managed by the National Elevator Standardization Technical Committee (SAC/TC196).

Drafting organizations of this section. Yongda Elevator Equipment (China) Co., Ltd., China Building Research Institute Co., Ltd. Construction Mechanization Research Branch Institute, Shanghai Mitsubishi Elevator Co., Ltd., Xizi Elevator Group Co., Ltd., Hitachi Elevator (China) Co., Ltd., Shanghai Jiaotong University Power Engineering College, Otis Elevator (China) Co., Ltd., Shanghai Special Equipment Supervision and Inspection Technology Research Institute, Guangdong Special Equipment Inspection Research Institute, China Special Equipment Inspection and Research Institute, KONE Elevator Co., Ltd., Schindler (China) Elevator Co., Ltd., National Elevator Quality Supervision and Inspection Inspection Center, CANNY Elevator Co., Ltd., Southeast Elevator Co., Ltd., ThyssenKrupp Elevator (Shanghai) Co., Ltd., Gansu Special Equipment Inspection and Testing Institute, Ningbo Shenling Electromechanical Technology Co., Ltd., Toshiba Elevator (China) Co., Ltd., Jiangsu Special Equipment Suzhou Branch of All Supervision and Inspection Research Institute, Yancheng Branch of Jiangsu Special Equipment Safety Supervision and Inspection Research Institute, Giant KONE Elevator Co., Ltd., Lingwang

Elevator Co., Ltd., Suzhou Jiangnan Jiajie Elevator Co., Ltd., Guangzhou Guangri Elevator Industry Co., Ltd., Shanghai Edenberg Elevator Group Co., Ltd., Hangzhou Theo Elevator Co., Ltd., Xizi Elevator Technology Co., Ltd., Guangdong Suzuki Elevator Co., Ltd., Suzhou Huichuan Technology Co., Ltd., Shanghai Modern Elevator Manufacturing Co., Ltd., Kunshan Tongyou Elevator Co., Ltd., Guangdong Huanyu Electronic Technology Co., Ltd., Sen He Elevator Co., Ltd.

Introduction

0.1 The purpose of this part of GB/T 24474 is to encourage the entire industry to define, measure, and measure the vibration and noise signals that constitute the quality of elevator transportation.

The processing and presentation are unified.

The purpose of unification is to reduce the difference in elevator ride quality measurement results caused by the difference in signal acquisition and quantification methods, so that Elevator users benefit.

0.2 This section is mainly used to provide guidance to groups interested in the following aspects.

- a) Improve the manufacturing specifications and calibration methods of the instrument;
- b) The scope of the elevator transportation quality and technical indicators is stipulated in the contract;
- c) Measure the elevator transportation quality according to national standards.

0.3 This section aims to propose such a method for measuring the quality of elevator transportation.

- a) It is easy to understand by people who have no professional knowledge in noise and vibration analysis;
- b) It is closely related to the human body's response to ensure that it can more truly reflect the human body's feelings;
- c) The measurement traceability of measurement results can be ensured through calibration procedures traceable to national standards.

0.4 The experience of the elevator industry shows that the assessment of peak-to-peak vibration is specifically related to passenger comfort. For this part, quantify Two forms of expression of maximum vibration peak-to-peak value and A95 vibration peak-to-peak value are necessary.

0.5 Due to the particularity of elevator products, it is necessary to specify the necessary conditions and methods for the measurement process and the quantification of each signal