



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 24610.4-2019

**Rolling bearings -- Measuring methods for vibration -- Part 4:
Radial cylindrical roller bearings with cylindrical bore and
outside surface**

Issued on: October 18, 2019

Implemented on: May 1, 2020

Issued by: SAMR; SAC

Table of Contents

Foreword	
Introduction	
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Measurement procedure	1
4.1 Rotation frequency	1
4.2 Bearing radial and axial loads	1
5 Measurement and evaluation methods	2
5.1 Measured physical quantities	2
5.2 Frequency domain	2
5.3 Pulse and sharp pulse measurement	3
5.4 Test	3
6 Measurement conditions	3
6.1 Bearing measurement conditions	3
6.2 Test environmental conditions	3
6.3 Test device conditions	4
Appendix A (Normative) Measurement of centering accuracy with applied radial load	8
Appendix B (Normative) Measurement of centering accuracy with applied axial load	9

Foreword

GB/T 24610 "Measurement method for rolling bearing vibration" is divided into 4 parts.

--- Part 1.Basics;

--- Part 2.Radial ball bearings with cylindrical holes and cylindrical outer surfaces;

--- Part 3.Spherical roller bearings and tapered roller bearings with cylindrical bore and cylindrical outer surface;

--- Part 4.Cylindrical roller bearings with cylindrical bore and cylindrical outer surface.

This part is Part 4 of GB/T 24610.

This section is drafted in accordance with the rules given in GB/T 1.1-2009.

This section replaces GB/T 24610.4-2009 "Method for measuring vibration of rolling

bearings. Part 4. Cylindrical holes and cylindrical appearance

Cylindrical Roller Bearings ", compared with GB/T 24610.4-2009, the main technical changes are as follows.

- Modified the lower cut-off frequency of the low frequency band with a rotation frequency of 900min⁻¹ (see Table 2, Table 2 of the 2009 edition);
- Added "Example of frequency range of non-set rotation frequency" table (see Table 3);
- Modified the description of the figure (see Figure 2, Figure 2 of the 2009 edition);
- Deleted the "requirements for operators" (see 6.3.6 of the 2009 version).
- Added description of some figures (see Figure A.1, Figure B.1).

This section uses translation method equivalent to ISO 15242-4:2017 Method for measuring vibration of rolling bearings. Part 4. with cylindrical hole

And cylindrical roller bearings with cylindrical outer surfaces.

The Chinese documents that have a consistent correspondence with the international documents referenced normatively in this section are as follows.

--- GB/T 1800.2-2009 Geometrical Product Specifications (GPS) Limits and Fits Part 2. Standard Tolerance Grades and

Hole and shaft limit deviation table (ISO 286-2:1988, MOD)

--- GB/T 2298-2010 Vocabulary for mechanical vibration, shock and condition monitoring (ISO 2041:2009, IDT)

--- GB/T 4199-2003 Tolerance definition of rolling bearings (ISO 1132-1:2000, MOD)

--- GB/T 6930-2002 Vocabulary for rolling bearings (ISO 5593:1997, IDT)

--- GB/T 24610.1-2019 Rolling bearing vibration measurement method Part 1. Basics (ISO 15242-1:2015, IDT)

This section is proposed by China Machinery Industry Federation.

This part is under the jurisdiction of the National Rolling Bearing Standardization Technical Committee (SAC/TC98).

This section was drafted by. Luoyang Bearing Research Institute Co., Ltd., Wuxi Wald Bearing Co., Ltd., Zhejiang Zhaofeng Electromechanical Co., Ltd.

Division, Shandong Camry Bearing Technology Co., Ltd., Fujian Yongan Bearing Co., Ltd., Dalian Baishengyuan Technology Co., Ltd., Hangzhou Bearing

Experimental Research Center Co., Ltd.

introduction

The vibration of a rolling bearing is an important operating characteristic. Vibration can affect the performance of a mechanical system with bearings. When vibration

When propagated to the environment in which the operating mechanical system is located, it can cause audible noise, which can lead to system damage and even health problems.

The vibration of a rolling bearing during rotation is a complex physical phenomenon related to the operating conditions. Single set of shafts measured under a set of conditions

The bearing vibration value does not necessarily represent the vibration value under different conditions or when the bearing becomes a part of a larger component. Assessed

The sound generated by the mechanical system of the bearing is more complicated. It is also affected by the interface conditions, the position and orientation of the sensing device, and the sound of the system.

Impact of the learning environment. Air noise-GB/T 24610 (all parts) is defined as any unpleasant, undesired sound.

Because the term "unpleasant, undesired" has a subjective nature, its evaluation is more complicated. It can be considered that the structural vibration of the bearing is

Eventually the driving source for air noise. GB/T 24610 (all parts) only includes vibration measurement of selected bearing structures

method.

Bearing vibration can be evaluated using any of a number of methods, with different evaluation methods using different types of sensors and test conditions.

No set of values characterizing bearing vibrations can evaluate bearing vibration performance under all possible conditions of use. Eventually, also

It should be based on known bearing types, conditions of use, and vibration testing purposes (e.g.

To choose the most suitable test method. Therefore, the scope of application of bearing vibration standards is not universal. But for the purposes of this section,

Only certain methods with a very broad scope are established as standard methods.

This section details the assessment of the vibration of single and double row cylindrical roller bearings with cylindrical bores and cylindrical outer surfaces on a test device

method.

Method for measuring vibration of rolling bearings

Part 4. Cylindrical holes and cylindrical outer surfaces

Cylindrical Roller Bearings

1 Scope

This part of GB/T 24610 specifies the vibration measurement methods of single-row and double-row cylindrical roller bearings under the established test conditions.

This section applies to single-row and double-row cylindrical roller bearings with cylindrical bore and cylindrical outer surface.

2 Normative references

The following documents are essential for the application of this document. For dated references, only the dated version applies to this article

Pieces. For undated references, the latest version (including all amendments) applies to this document.

ISO 286-2 Geometric Product Specifications (GPS) Linear Dimensional Tolerance ISO Code System Part 2. Standard Tolerance Classes and

Hole and shaft limit deviation table [Geometrical product specifications (GPS) - ISO code system for tolerances on

linear sizes - Part 2. Tables of standard tolerance grades and limit deviations for holes and shafts]

ISO 1132-1 Rolling bearing tolerances - Part 1. Terms and definitions

Terms and definitions)

ISO 2041 Vocabulary for Mechanical Vibration, Shock and Condition Monitoring (Mechanical vibration, shock and condition monitoring -

ring - Vocabulary)

ISO 5593 rolling bearing vocabulary (Rolling bearings - Vocabulary)

ISO 15242-1..2015 Rolling bearing vibration measurement methods - Part 1. Basics (Rolling bearings - Measuring

methods for vibration - Part 1. Fundamentals)

3 terms and definitions

Terms and definitions defined in ISO 1132-1, ISO 2041, ISO 5593 and ISO 15242-1 apply to this document.