

ICS 23.100.40



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 25133-2010

**Hydraulic fluid power systems -- Assembled systems --
Methods of cleaning lines by flushing**

液压系统总成 管路冲洗方法

(English Translation)

Issued on: September 26, 2010

Implemented on: February 1, 2011

Issued by: SAMR; SAC

Table of Contents

1	Scope
2	Normative references
3	Terms and definitions
3.1	Flushing
3.2	External flushing outflushing
3.3	Visual cleanliness visiblecleanliness
3.4	Clean work area cleanworkarea
5	Flushing of the pipeline in the hydraulic system
5.1	Influencing factors
5.2	System Design
5.3	Component cleanliness level
5.4	Preservatives
6.1	Preparation of piping during manufacturing
6.2	Surface treatment
6.3	Storage of pipes and joints
7	Hydraulic line installation
8	Flushing requirements
8.1	General
8.2	Clearing inner surface particles
8.2.2	Re and required flow (qV) can be calculated using equations (1) and (2).
8.3	Separation of filters and particles
8.3.1	General requirements
8.3.2	Auxiliary Flushing Filter
8.4	Minimum rinse time
8.4.2	The recommended minimum rinse time (t) can be calculated using equation (3).
9	Final cleanliness test
10	Description of the label (citing this standard)

What is delivered

The English PDF of this standard, delivered to your email address.

Instant delivery: the file is sent automatically after payment.