

ICS 21.200
CCS J17



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 3480.2-2021

**Calculation of load capacity of spur and helical gears - Part 2:
Calculation of surface durability(pitting)**

直齿轮和斜齿轮承载能力计算 第2部分：齿面接触强度（点蚀）计算
(English Translation)

Issued on: March 9, 2021

Implemented on: October 1, 2021

**Issued by: State Administration for Market Regulation, China National
Standardization Administration**

Table of Contents

1	Scope
2	Normative references
3	Terms, definitions, symbols and abbreviations
3.1	Terms and definitions
3.2	Symbols and abbreviations
4	Pitting damage and safety factor
5	Basic formula
5.1	Overview
5.2	Safety factor S_H 6 of tooth surface contact strength (pitting corrosion)
5.3	Calculated value of contact stress σ_H
5.4	Allowable contact stress σ_{HP}
5.4.1	Overview
5.4.3	Determination of allowable contact stress σ_{HP} . Method B
6	Node area coefficient Z_H and single pair of tooth meshing coefficients Z_B and Z_D
6.1	Overview
6.2	Determination of node area coefficient Z_H
6.2.1	Overview
6.2.2	Graphical values
6.2.3	Analytical value
6.3	When $\alpha \leq 20^\circ$, the determination of the meshing coefficients Z_B and Z_D
6.4	When $\alpha > 20^\circ$, the determination of the meshing coefficients Z_B and Z_D
7	Elasticity coefficient Z_E
8	Coincidence coefficient Z_γ
8.1	Overview
8.2	Determination of the coincidence coefficient Z_γ
8.2.1	Graphical values
8.2.2	Analytical value
8.3	Determination of end-face coincidence γ_a and axial coincidence γ_f
8.3.1	End-face coincidence γ_a
8.3.2	Axial coincidence γ_f
9	Helix angle coefficient Z_β
10	Contact fatigue limit of test gear

10.1 Overview	
10.2 Contact fatigue limit σ_{Hlim} in Method B	
10.3 Contact fatigue limit value in method BR	
11 Life factor ZNT (tooth surface)	
11.1 Overview	
11.2 Life factor ZNT. Method A	
11.3 Life factor ZNT. Method B	
12 Lubricating oil film influence coefficient ZL, Zv and ZR	
12.1 Overview	
12.2 The effect of lubricating oil film. Method A	
12.3 Lubricating oil film influence coefficients ZL, Zv and ZR. Method B	
12.3.1 Overview	
12.3.2 ZL, Zv and ZR at the limit of contact durability	
12.3.3 Lubricating oil influence coefficients ZL, Zv and ZR under static strength	
13 Working hardening coefficient of tooth surface ZW	
13.1 Overview	
13.2 Tooth surface working hardening factor ZW. Method A	
13.3 Tooth surface working hardening factor ZW. Method B	
13.3.1 Pairing of hardened small gears with hardened and tempered large gears	
13.3.2 Pairing of quenched and tempered small gear and quenched and tempered large gear	
13.3.3 Pairing of case-hardened small gears with nodular cast iron large gears	
14 Size factor ZX	
1 Scope	
2 Normative references	
3 Terms, definitions, symbols and abbreviations	
3.1 Terms and definitions	
5 Basic formula	
5.1 Overview	
5.2 Safety factor SH of tooth surface contact strength (pitting corrosion)	
5.3 Calculated value of contact stress σ_H	
5.4 Allowable contact stress σ_{HP}	
5.4.1 Overview	
5.4.2.1 Overview	
5.4.2.2 Method A	

5.4.2.3 Method B

5.4.2.4 Method BR

5.4.3 Determination of allowable contact stress σ_{HP} . Method B

12.3.3 Lubricating oil influence coefficients Z_L , Z_v and Z_R under static strength

13 Tooth surface work hardening coefficient Z_W

13.1 Overview

13.2 Tooth surface working hardening coefficient Z_W . Method A

13.3 Tooth surface working hardening factor Z_W . Method B

13.3.1 Pairing of hardened small gears with hardened and tempered large gears

13.3.1.1 Overview

13.3.1.2 Graphical value of Z_W for durability limit and contact stress under high cycle fatigue

What is delivered

The English PDF of this standard, delivered to your email address.

Instant delivery: the file is sent automatically after payment.