

ICS 31.080.10, 31.080.30
CCS L 45



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 4023.4-2026

Replacing GB/T 20516-2006

**Discrete semiconductor devices - Part 4: Microwave diodes and
transistors**

半导体分立器件 第4部分：微波二极管和晶体管

(English Translation)

Issued on: April 30, 2026

Implemented on: November 1, 2026

Issued by: State Administration for Market Regulation

Table of Contents

Preface

Introduction

1 Scope

2 Normative References

3 Terms and Definitions

3.1 Microwave Diode

3.2 Transistors

4 Varactor Diodes

4.1 Overview

4.2 Basic Ratings and Characteristics

4.2.1 Rated value

4.2.2 Feature

4.3 Test Method

4.3.1 Total capacitance C_t

4.3.2 Reverse current I_R

4.3.3 Reverse breakdown voltage V_{BR}

4.3.4 Forward differential resistor r_F

4.3.5 Steady-state thermal resistance R_{th}

4.3.6 Series inductor L_s

4.3.7 Quality Factor Q_{19}

4.3.8 Series resistance R_s

4.3.9 Cutoff frequency f_c

5-step diode

5.1 Overview

5.2 Basic ratings and characteristics

5.2.1 Rated value

5.2.2 Feature

5.3 Test Method

5.3.1 Distributed capacitance C_P , junction capacitance C_j , and total capacitance C_t

5.3.2 Reverse current I_R

5.3.3 Reverse breakdown voltage V_{BR}

5.3.4 Forward voltage V_F

5.3.5 Forward differential resistor r_F

5.3.6 Steady-state thermal resistance R_{th}

5.3.7 Series inductor L_s

5.3.8 Series resistor R_s

5.3.9 Minority carrier lifetime τ

5.3.10 Step time t_{st}

6 Mixer diodes

6.1 Overview

6.2 Basic ratings and characteristics

6.2.1 Rated value

6.2.2 Feature

6.3 Test Method

6.3.1 Distributed capacitance C_P , junction capacitance C_j , and total capacitance C_t

6.3.2 Reverse current I_R

6.3.3 Reverse breakdown voltage V_{BR}

6.3.4 Forward voltage V_F

6.3.5 Forward differential resistor r_F

6.3.6 Dynamic Resistance R_D

6.3.7 Series inductor L_s

6.3.8 Series resistor R_s (mixer diode)

6.3.9 Noise Figure NF

6.3.10 Intermediate Frequency Impedance Z_{if}

6.3.11 Voltage Standing Wave Ratio (VSWR)

6.3.12 Variable frequency drive loss L_c

6.3.13 Output noise ratio N_r

6.3.14 Maximum power withstandable. P_m

7 Detector diode

7.1 Overview

7.2 Basic Ratings and Characteristics

7.2.1 Rated value

7.2.2 Feature

7.3 Test Method

7.3.1 Distributed capacitance C_P , junction capacitance C_j , and total capacitance C_t

7.3.2 Reverse current I_R

7.3.3 Reverse breakdown voltage V_{BR}

- 7.3.4 Forward voltage V_F
- 7.3.5 Forward differential resistor r_F
- 7.3.6 Dynamic Resistance R_D
- 7.3.7 Series resistor R_s
- 7.3.8 Video resistor R_v
- 7.3.9 Voltage sensitivity S_v
- 7.3.10 Current sensitivity S_i
- 7.3.11 Tangent Sensitivity (TSS)
- 7.3.12 Maximum power withstand capability P_m
- 8-Body Effect Diode
 - 8.1 Overview
 - 8.2 Basic Ratings and Characteristics
 - 8.2.1 Rated value
 - 8.2.2 Feature
 - 8.3 Test Method
 - 8.3.1 Low field resistance R_0
 - 8.3.2 Threshold current I_{th} , threshold voltage V_{th}
 - 8.3.3 Pulse breakdown voltage V_{BR}
 - 8.3.4 Thermal resistance R_{th} (bulk effect diode)
 - 8.3.5 Microwave output power P_o , frequency f , efficiency η
- 9-pin diode
 - 9.1 Overview
 - 9.2 Basic ratings and characteristics
 - 9.2.1 Rated value
 - 9.2.2 Feature
 - 9.3 Test Method
 - 9.3.1 Distributed capacitance C_P , junction capacitance C_j , and total capacitance C_t
 - 9.3.2 Reverse current I_R
 - 9.3.3 Reverse breakdown voltage V_{BR}
 - 9.3.4 Forward voltage V_F
 - 9.3.5 Forward differential resistor r_F
 - 9.3.6 Steady-state thermal resistance R_{th}
 - 9.3.7 Transient thermal resistance Z_{th}
 - 9.3.8 Series resistance R_s
 - 9.3.9 Minority carrier lifetime τ

9.3.10 Effective minority carrier lifetime

9.3.11 Reverse recovery time t_{rr}

10 Noise diodes

10.1 Overview

10.2 Basic ratings and characteristics

10.2.1 Rated value

10.2.2 Feature

10.3 Test Method

10.3.1 Distributed capacitance C_P , junction capacitance C_j , and total capacitance C_t

10.3.2 Reverse Current I_R

10.3.3 Reverse breakdown voltage V_{BR}

10.3.4 Forward voltage V_F

10.3.5 Forward differential resistor r_F

10.3.6 Reverse Differential Resistor r_R

10.3.7 Over-noise ratio (ENR)

11 Bipolar Transistors

11.1 Overview

11.2 Basic Ratings and Characteristics

11.2.1 Overview

11.2.2 Limits (Absolute Maximum Rated Value System)

11.3 Test Method

11.3.1 Overview

11.3.2 DC Characteristics

11.3.3 Radio Frequency Characteristics

11.4 Verification Method

11.4.1 Load Mismatch Tolerance (ψ_{iL})

11.4.2 Source mismatch tolerance (ψ_{iS})

11.4.3 Load mismatch without damage (ψ_{iR})

12 Field-Effect Transistors

12.1 Overview

12.2 Basic Ratings and Characteristics

12.2.1 Overview

12.2.2 Limits (Absolute Maximum Rated Value System)

12.3 Test Methods

12.3.1 Overview