



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 40822-2021

Road vehicles - Unified diagnostic services

道路车辆 统一的诊断服务

(English Translation)

Issued on: October 11, 2021

Implemented on: May 1, 2022

Issued by: SAMR; SAC

Table of Contents

Foreword	16
Introduction	18
1 Scope	20
2 Normative references	20
3 Terms, definitions and abbreviations	22
3.1 Terms and definitions	22
3.2 Abbreviations	26
4 Conventions	29
5 Overview	30
6 Application layer	31
6.1 Application layer services	31
6.1.1 General	31
6.1.2 Format description of application layer services	33
6.1.3 Format description of service primitives	34
6.1.3.1 General definition	34
6.1.3.2 Service request and service indication primitives	34
6.1.3.3 Service response and service confirm primitives	35
6.1.3.4 Service request-confirm and service response-confirm primitives	36
6.1.4 Service data unit specification	37
6.1.4.1 Mandatory parameters	37
6.1.4.2 Vehicle system requirements	40
6.1.4.3 Optional parameters - A_AE, application layer remote address	40
6.2 Application layer protocol	41
6.2.1 General definition	41
6.2.2 A_PDU, application protocol data unit	42
6.2.3 A_PCI, protocol control information	42
6.2.4 SI, service identifier	43
6.2.5 A_NR_SI, Negative response service identifier	44
6.2.6 Negative response/confirmation service primitive	45
6.2.7 Server response implementation rules	45
6.2.7.1 General definitions	45
6.2.7.2 General server response behaviour	46

behaviour	54
6.2.7.5 Pseudo code example of server response behaviour	56
addressing	58
6.3 Service description conventions	59
6.3.1 Service description	59
6.3.2 Request message	59
6.3.2.1 Request message definition	59
6.3.2.2 Request message SubFunction parameter \$Level (LEV_) definition	60
6.3.2.3 Request message data-parameter definition	62
6.3.3 Positive response message	63
6.3.3.1 Positive response message definition	63
6.3.3.2 Positive response message data-parameter definition	64
6.3.4 Supported negative response codes (NRC_)	64
6.3.5 Message flow examples	65
6.4 Diagnostic and communication management functional unit	66
6.4.1 Overview	66
6.4.2 DiagnosticSessionControl (1016) service	66
6.4.2.1 Service description	66
6.4.2.2 Request message	70
6.4.2.3 Positive response message	72
6.4.2.4 Supported negative response codes (NRC_)	73
programmingSession	74
6.4.3 ECUReset (1116) service	75
6.4.3.1 Service description	75
6.4.3.2 Request message	75
6.4.3.3 Positive response message	77
6.4.3.4 Supported negative response codes (NRC_)	78
6.4.3.5 Message flow example ECUReset	78
6.4.4 SecurityAccess (2716) service	79
6.4.4.1 Service description	79
6.4.4.2 Request message	81
6.4.4.3 Positive response message	83
6.4.4.4 Supported negative response codes (NRC_)	84
6.4.4.5 Message flow example(s) SecurityAccess	85
6.4.5 CommunicationControl (2816) service	87

6.4.5.1 Service description	87
6.4.5.2 Request message	87
6.4.5.3 Positive response message	89
6.4.5.4 Supported negative response codes (NRC_)	89
network management messages)	90
connected to)	90
connected to a sub-network, is addressed)	91
6.4.6 Authentication (2916) service	92
6.4.6.1 Service overview	92
6.4.6.2 Authentication with PKI Certificate Exchange (APCE)	93
6.4.6.3 Authentication with Challenge-Response (ACR)	99
6.4.6.4 Common requirements	105
6.4.6.5 Request message	106
6.4.6.6 Positive response message	115
6.4.6.7 Supported negative response codes (NRC_)	123
6.4.6.8 Message flow example(s) Authentication	124
6.4.7 TesterPresent (3E16) service	148
6.4.7.1 Service description	148
6.4.7.2 Request message	148
6.4.7.3 Positive response message	149
6.4.7.4 Supported negative response codes (NRC_)	149
6.4.7.5 Message flow example(s) TesterPresent	150
6.4.8 ControlIDTCSetting (8516) service	151
6.4.8.1 Service description	151
6.4.8.2 Request message	151
6.4.8.3 Positive response message	153
6.4.8.4 Supported negative response codes (NRC_)	153
6.4.8.5 Message flow example(s) ControlIDTCSetting	153
6.4.9 ResponseOnEvent (8616) service	155
6.4.9.1 Service description	155
6.4.9.2 Request message	163
6.4.9.3 Positive response message	171
6.4.9.4 Supported negative response codes (NRC_)	174
6.4.9.5 Message flow example(s) ResponseOnEvent	175
6.4.10 LinkControl (8716) service	192

6.4.10.1 Service description	192
6.4.10.2 Request message	193
6.4.10.3 Positive response message	195
6.4.10.4 Supported negative response codes (NRC_)	196
6.4.10.5 Message flow example(s) LinkControl	196
6.5 Data transmission functional unit	199
6.5.1 Overview	199
6.5.2 ReadDataByIdentifier (2216) service	200
6.5.2.1 Service description	200
6.5.2.2 Request message	200
6.5.2.3 Positive response message	201
6.5.2.4 Supported negative response codes (NRC_)	202
6.5.2.5 Message flow example ReadDataByIdentifier	204
6.5.3 ReadMemoryByAddress (2316) service	207
6.5.3.1 Service description	207
6.5.3.2 Request message	207
6.5.3.3 Positive response message	208
6.5.3.4 Supported negative response codes (NRC_)	209
6.5.3.5 Message flow example ReadMemoryByAddress	211
6.5.4 ReadScalingDataByIdentifier (2416) service	214
6.5.4.1 Service description	214
6.5.4.2 Request message	214
6.5.4.3 Positive response message	215
6.5.4.4 Supported negative response codes (NRC_)	216
6.5.4.5 Message flow example ReadScalingDataByIdentifier	217
6.5.5 ReadDataByPeriodicIdentifier (2A16) service	221
6.5.5.1 Service description	221
6.5.5.2 Request message	225
6.5.5.3 Positive response message	226
6.5.5.4 Supported negative response codes (NRC_)	227
6.5.5.5 Message flow example ReadDataByPeriodicIdentifier	230
6.5.6 DynamicallyDefineDataIdentifier (2C16) service	244
6.5.6.1 Service description	244
6.5.6.2 Request message	246
6.5.6.3 Positive response message	250