

ICS 29.130.10
CCS K 43



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 45932-2025

**Common specifications for high-voltage direct current
switchgear and controlgear standards
(English Translation)**

Issued on: June 30, 2025

Implemented on: January 1, 2026

**Issued by: State Administration for Market Regulation, China National
Standardization Administration**

Table of Contents

Preface
1 Scope
2 Normative references
3 Terms and Definitions
3.1 General Terms and Definitions
3.2 Assembly of switchgear and controlgear
3.3 Components of the final assembly
3.4 Switchgear
3.5 Components of switchgear and controlgear
3.6 Operating characteristics of switchgear and controlgear
3.7 Characteristic parameters
4 Normal and special conditions of use
4.1 Normal use conditions
4.2 Special conditions of use
5 Rating
5.1 General Principles
5.2 Rated DC voltage (U_{rd})
5.3 Rated insulation level (U_{dd} , U_p and U_s)
5.4 Rated continuous current (I_{rd})
5.5 Short-time withstand current rating
5.6 Rated supply voltage of auxiliary and control circuits (U_a)
5.7 Rated frequency of auxiliary and control circuit supply voltage
5.8 Rated pressure of compressed gas source for controlled pressure system
6 Design and Structure
6.1 Requirements for liquids in switchgear and controlgear
6.2 Gas requirements for switchgear and controlgear
6.3 Grounding of switchgear and controlgear
6.4 Auxiliary and control equipment and circuits
6.5 Power Operation
6.6 Energy Storage Operation
6.7 Operations that do not rely on non-locking (operations that do not rely on manpower or power)

- 6.8 Human-operated actuators
- 6.9 Trip Unit Operation
- 6.10 Pressure/Liquid Level Indicator
- 6.11 Nameplate
- 6.12 Interlocking device
- 6.13 Position indication
- 6.14 Degree of protection provided by enclosure
- 6.15 Selection of Outdoor Insulators
- 6.16 Gas and vacuum sealing
- 6.17 Liquid Sealing
- 6.18 Fire (flammability)
- 6.19 Electromagnetic Compatibility (EMC)
- 6.20 X-ray emission
- 6.21 Corrosion
- 6.22 Insulation and/or switching, operating filling pressure/level
- 7 Type test
 - 7.1 General Principles
 - 7.2 Insulation test
 - 7.3 Loop resistance measurement
 - 7.4 Continuous current test
 - 7.5 Short-time withstand current and peak withstand current test
 - 7.6 Protection level verification
 - 7.7 Sealing test
 - 7.8 Electromagnetic compatibility test (EMC)
 - 7.9 Additional tests on auxiliary and control circuits
 - 7.10 X-ray test of vacuum interrupter
- 8 Factory test
 - 8.1 General Principles
 - 8.2 Insulation test of main circuit
 - 8.3 Tests of auxiliary and control circuits
 - 8.4 Measurement of main circuit resistance
 - 8.5 Sealing test
 - 8.6 Design Inspection and Appearance Inspection
- 9 Guidelines for the selection of switchgear and controlgear
 - 9.1 Overview

9.2 Selection of Ratings	
9.3 Cable Interface	
9.4 Continuous and temporary overloads caused by changes in operating conditions	
9.5 Environmental aspects	
10 Information provided when making inquiries, bidding and placing orders	
10.1 General Principles	
10.2 Inquiry and Order Information	
10.3 Bidding Documents	
11 Rules for transportation, storage, installation, operation and maintenance	
11.1 General Principles	
11.2 Conditions during transportation, storage and installation	
11.3 Installation	
11.4 Run	
11.5 Maintenance	
12 Safety	
12.1 Overview	
12.2 Precautions by the manufacturer	
12.3 Precautions for users	
13 Impact of products on the environment	72
Appendix A (Informative) Example of Layout of Single-Pole Valve-Side Switchgear in HVDC Converter Stations	
Appendix B (Informative) Pollution Level	
B.1 Overview	
B.2 Degree of filth	
Appendix C (Normative) Preferred insulation levels for rated voltages below 105 kV	
Appendix D (Informative) HVDC system short-circuit current	
D.1 VSCHVDC	
D.2 LCCHVDC	
D.3 LCCHVDC DC Fault Special Case	
D.4 HVDC systems with DC circuit breakers	
D.5 Calculation of rated short-time withstand DC current	
D.6 Calculation of Joule Integral (E_j)	
Appendix E (Informative) Standards for Auxiliary and Control Circuit Components	
Appendix F (Informative) List of Symbols	
Appendix G (Normative) Rainproof test method for outdoor switchgear and control equipment	

Appendix H (Normative) Tolerances of test parameters during the test

Appendix I (Informative) Extension of Type Test Validity

I.1 Overview

I.2 Insulation test

I.3 Short-time withstand current and peak withstand current test

I.4 Immunity test for auxiliary and control circuits

I.5 Environmental testing of auxiliary and control circuits

Appendix J (Normative) Confirmation of test sample

J.1 General Principles

J.2 Data

J.3 Drawing

Appendix K (Informative) Superimposed impulse voltage test circuit

K.1 Overview

K.2 Test circuit using DC blocking capacitors

K.3 Test circuit using a spherical gap

Appendix L (Normative) Information and technical requirements for enquiries, tenders and orders

L.1 General Principles

L.2 Normal and special conditions of use (see Chapter 4)

L.3 Rated value (see Chapter 5)

L.4 Design and construction (see Chapter 6)

L.5 System Information

L.6 Inquiry and Bid Documents

Appendix M (Informative) Field Measurement of Electromagnetic Compatibility

Reference

Figure 1 Typical waveform of short-circuit current in a HVDC system

Figure 2 Example of contact rating

Figure 3 Connection diagram of switch device

Figure 4 Schematic diagram of superimposed impulse voltage test

Figure 5 Test sequence for polarity reversal test

Figure 6 Test circuit diagram for radio interference voltage test

Figure 7 Location of the radiation measuring instrument

Figure A.1 Example of switchgear arrangement on the single-pole HVDC side of an HVDC converter station

Figure D.1 Worst-case VSCHVDC, pole-to-pole DC fault

Figure D.2 Worst-case LCCHVDC, pole-to-pole DC fault