

ICS 31.060.70
CCS K 42



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 47158-2026

**Shunt power capacitors of the self-healing type for AC systems
having a rated voltage above 1 000 V**

标称电压1000 V以上交流系统用自愈式并联电力电容器

(English Translation)

Issued on: February 27, 2026

Implemented on: June 1, 2026

Issued by: State Administration for Market Regulation

Table of Contents

Preface	
1 Scope	
2 Normative References	
3 Terms and Definitions	
4 Usage conditions 5.	
4.1 Normal operating conditions	
4.2 Abnormal usage conditions	
5 Quality and Testing Requirements 6.	
5.1 General Rules	
5.2 Test Conditions	
6 Test Classification	
6.1 Routine Tests	
6.2 Type testing and design testing	
6.3 Acceptance Test	
7 Capacitance Measurement (Routine Test) 8.	
7.1 Measurement Procedure	
7.2 Capacitance deviation	
8 Capacitor Loss Tangent ($\tan\delta$) Measurement (Routine Test)	
8.1 Measurement Procedure	
8.2 Capacitor Loss Tangent ($\tan\delta$) Requirement	
9 Inter-terminal voltage test	
9.1 General Rules for Routine Testing	
9.2 AC Test	
9.3 DC Test	
9.4 Type Testing	
10 AC voltage test between terminals and housing	
10.1 Routine Tests	
10.2 Type Testing	
11 Internal Discharge Device Testing (Routine Test)	
12 Sealing test (routine test)	
13 Thermal stability test (type test)	
13.1 Overview	

- 13.2 Measurement Procedure
- 14 Measurement of capacitor loss tangent ($\tan\delta$) at high temperature (type test)
 - 14.1 Measurement Procedure
 - 14.2 Requirement
- 15 Lightning impulse voltage test between terminals and enclosure (type test)
- 16 Overvoltage Test (Design Test)
 - 16.1 General Rules
 - 16.2 Stabilization treatment of samples before testing
 - 16.3 Test Procedure
 - 16.4 Acceptance Criteria
 - 16.5 Validity of the experiment
 - 16.5.1 General Rule
 - 16.5.2 Component Design
 - 16.5.3 Experimental Unit Design
 - 16.5.4 Overvoltage waveform
- 17 Short-circuit discharge test (type test)
- 18 Self-healing test (type test)
 - 18.1 General Rules
 - 18.2 Test Procedure
 - 18.3 Acceptance Criteria
- 19 Destructive Testing (Designed Experiments)
 - 19.1 General Rules
 - 19.2 Test Procedure for Capacitors Without Active Monitoring Safety Devices (Internal Protection)
 - 19.3 Acceptance Criteria
 - 19.4 Test Procedures for Capacitors with Active Monitoring Safety Devices (External Protection)
 - 19.5 Acceptance Criteria
- 20 Insulation level
 - 20.1 Standard insulation value
 - 20.2 General Requirements
 - 20.2.1 General Rule
 - 20.2.2 Adjacent insulating components and equipment
 - 20.2.3 Ground-insulating capacitor
 - 20.2.4 Neutral point grounding capacitor
 - 20.3 Test between capacitor unit terminals and housing

- 20.4 Capacitors in a Single-Phase System
- 21 Overload --- Maximum permissible voltage
 - 21.1 Long-term voltage
 - 21.2 Operating overvoltage
- 22 Overload --- Maximum permissible current
- 23 Safety requirements for discharge devices
- 24 Safety requirements for enclosure connections
- 25 Environmental protection safety requirements
- 26 Other safety requirements
- 27 Markings of capacitor cells
 - 27.1 Nameplate
 - 27.2 Standardized Connection Symbols
 - 27.3 Warning sign
- 28 Markings for capacitor banks 22.
 - 28.1 Instruction manual or nameplate
 - 28.2 Warning sign
- 29 Installation and Operation Guidelines
 - 29.1 General Rule
 - 29.2 Selection of Rated Voltage
 - 29.3 Operating temperature
 - 29.3.1 General Rule
 - 29.3.2 Installation
 - 29.3.3 High ambient air temperature
 - 29.4 Special Usage Conditions
 - 29.5 Overvoltage
 - 29.5.1 General Rule
 - 29.5.2 Switch breakdown due to heavy impact
 - 29.5.3 Lightning
 - 29.5.4 Self-excitation of electric motors
 - 29.5.5 Star-Delta Start
 - 29.5.6 Selection of Capacitor Units
 - 29.6 Overcurrent
 - 29.6.1 Continuous overcurrent
 - 29.6.2 Transient overcurrent
 - 29.7 Switches and protective devices

- 29.7.1 Tolerance Requirements
- 29.7.2 Circuit breakers without repeated breakdown
- 29.7.3 Relay Setting
- 29.8 Selection of Insulation Level
 - 29.8.1 Overview
 - 29.8.2 Altitude exceeding 1000m
 - 29.8.3 The Influence of the Capacitor Itself
 - 29.8.4 Overhead ground wire
- 29.9 Selection of Creepage Distance and Air Clearance
 - 29.9.1 Creepage Distance
 - 29.9.2 Air gap distance
- 29.10 The capacitor is connected to a system with audio remote control.
- Appendix A (Normative) Requirements for the Design of Comparable Components and Test Units
 - A.1 Test Element Design Criteria
 - A.2 Experimental Unit Design
- Appendix B (Informative) Self-healing breakdown testing equipment available for practical use
- Appendix C (Normative) Test Requirements and Application Guidelines for External Fuses and Units Protected by External Fuses
 - C.1 General Rule
 - C.2 Performance Requirements
 - C.3 Fuse Test
 - C.4 Guidelines for Coordination of Fuse Protection
 - C.4.1 General Rule
 - C.4.2 Protection Sequence
 - C.5 Selection of Fuse
 - C.5.1 General Rule
 - C.5.2 Non-current limiting fuse
 - C.5.3 Current-limiting fuse
 - C.6 Fuse User-Required Information
- Appendix D (Informative) Calculation Formulas for Capacitors and Devices
 - D.1 Calculate the three-phase capacitor capacity using the three capacitances measured between every two line terminals.
 - D.2 Resonant frequency
 - D.3 Voltage increased by