

ICS 47.020.50
CCS U 21



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 47733-2026

**Ships and marine technology - Ship's mooring and towing
fittings - Seats for closed chocks**

船舶和海上技术 船舶系泊和拖带设备 闭式导缆孔底座

(English Translation)

Issued on: May 25, 2026

Implemented on: September 1, 2026

Issued by: State Administration for Market Regulation

Table of Contents

- Foreword
- 1 Scope
- 2 Normative references
- 3 Terms and Definitions
- 4 Classification

Foreword

This document complies with the provisions of GB/T 1.1-2020 "Standardization Work Guidelines Part 1: Structure and Drafting Rules of Standardization Documents".

This document is equivalent to ISO 23113:2020 "Ships and marine technology - mooring and towing equipment for ships - closed cable guide base".

1 Scope

This document specifies the types, nominal dimensions, materials, and structures of closed-type cable guide bases used for guiding ship mooring and towing cables. Manufacturing and inspection, marking requirements.

2 Normative references

The contents of the following documents, through normative references within the text, constitute essential provisions of this document. Dated citations are not included.

For references to documents, only the version corresponding to that date applies to this document; for undated references, the latest version (including all amendments) applies. This document. mooring equipment)

3 Terms and Definitions

The following terms and definitions apply to this document.

3.1 Safeworkingload;SWL

Safety load limits (maximum permissible load) for mooring and towing equipment.

4.1 Type

Closed cable guide hole bases should be classified into the following types according to the installation location.

- a) Type A. Deck-mounted closed cable guide hole base;
- b) Type B. Closed cable guide base installed on the deck and sides;
- c) Type C. Closed cable guide elbow plate installed on the bulwark.

4.2 Nominal Dimensions

The nominal dimensions of the closed cable guide base are indicated with reference to the corresponding nominal dimensions of the closed cable guide (ISO 23113:2020). For those with... Closed cable guide bases of the same size but with different safe working loads are distinguished by adding the letters A, B or C after the nominal size. The nominal dimensions are as follows.

250x200x214, 300x250x286, 350x250x333, 400x250x381, 450x250x381, 500x250x381,
400x250x428, 450x250x428, 500x250x428, 500x400x428, 500x250x525A, 500x400x525A
500x250x525B, 500x400x525B