



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 5013.1-2008

Replacing GB 5013.1-1997

**Rubber insulated cables of rated voltages up to and including
450/750 V -- Part 1: General requirements**

额定电压450/750V及以下橡皮绝缘电缆 第1部分：一般要求

(English Translation)

Issued on: January 22, 2008

Implemented on: September 1, 2008

Issued by: SAMR; SAC

Table of Contents

1 Overview	
1.1 Scope	
1.2 Normative references	
2 Terms and definitions	
2.1 Insulation and sheathing material definition	
2.1.1 The mixture is classified according to the measured properties of the prescribed test.	
2.2 Test definition	
3.1 Origin signs and cable identification	
3.2 Rub resistance	
4.1 Insulation core color recognition	
4.1.1 General requirements	
4.2.1 General requirements	
4.2.3 Rub resistance	
5.1 Conductor	
5.1.1 Materials	
5.1.2 Structure	
5.1.3 Isolation between conductor and insulation	
5.2 Insulation	
5.2.1 Materials	
5.2.3 Thickness	
5.2.4 Mechanical properties before and after aging	
1 Tensile strength and elongation at break 2951.1-1997 9.1	
1.1.1 Tensile strength of the original value	
1.1.2 The original value of elongation at break	
1.2.2 Tensile strength after aging	
1.2.3 Elongation at break after aging	
1.4.1 Aging conditions a	
1.4.2 Tensile strength after aging	
1.4.3 Elongation at break after aging	
2 Thermal elongation test 2951.5-1997 Chapter 9	
2.1 Test conditions	

3.1 Test conditions

4.1 Test conditions

5.3.1 Materials

5.3.2 Cover

5.4 Spinning weaving

5.4.1 Materials

5.5.1 Materials

5.5.2 Cover

5.5.2.1 Single-layer sheath

5.5.3 Thickness

5.5.4 Mechanical properties before and after aging

1 Tensile strength and elongation at break 2951.1-1997 9.2

1.2.1 Aging conditions

1.3 Immersed mineral oil after the mechanical properties 2951.5-1997 10

1.3.1 Test conditions

2 Thermal elongation test 2951.5-1997 9

5.6.1 Electrical performance

What is delivered

The English PDF of this standard, delivered to your email address.

Instant delivery: the file is sent automatically after payment.