

ICS 29.060.01

CCS K 12



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 6109.19-2008

**Enamelled round winding wire -- Part 19: Polyester or
polyesterimide overcoated with polyamide-imide enamelled
round copper wire, class 200, with a bonding layer**

漆包圆绕组线 第19部分:200级自粘性聚酰胺酰亚胺复合聚酯或聚酯亚胺漆包铜圆
线

(English Translation)

Issued on: April 23, 2008

Implemented on: December 1, 2008

Issued by: Standardization Administration of China

Table of Contents

Introduction

1 Scope

2 Normative references

3 Definitions, test methods and appearance General

Size 4

5 Resistance

2 6 Elongation

2 7 resilience

8 Flexibility and adhesion

9 Thermal Shock

10 Softening

11 Scratch (conductor nominal diameter 0.250mm and 1.600mm above and below)

12 Solvent

13 Breakdown Voltage

14 Film continuity

15 Temperature index

16 Anti-freezing agent

17 Solderable

18 Thermal bonding

19 4 dielectric loss factor

20 Transformer oil resistant

21 4 Loss

23 Pinhole test

30 Package

Foreword

GB/T 6109 "enamelled round winding wires" is divided into 22 parts.

--- Part 1. General requirements;

--- Part 2. 155 polyester enamelled round copper wire;

--- Part 3. 120 acetal enamelled round copper wire;

- Part 4. 130 solderable polyurethane enamelled round copper wire;
- Part 5. 180 polyester enamelled round copper wire;
- Part 6. 220 Polyimide enamelled round copper wire;
- Part --- Article 7. 130L grade polyester enamelled round copper wire;
- Part 9. 130 polyamide composite solderable polyurethane enamelled round copper wire;
- Part 10. 155 solderable polyurethane enamelled round copper wire;
- Part 11. 155 polyamide composite solderable polyurethane enamelled round copper wire;
- Part 12. 180 polyester or polyamide, polyester enamelled round copper wire;
- Part 13. 180 solderable polyester-imide enamelled round copper wire;
- Part 14. Polyamide-imide 200 enamelled round copper wire;
- Part 15. 130 self-adhesive straight welding polyurethane enamelled round copper wire;
- Part 16. 155 self-adhesive straight welding polyurethane enamelled round copper wire;
- Part 17. 180 self-adhesive Solderable polyesterimide enamelled round copper wire;
- Part 18. 180 self-adhesive polyester enamelled round copper wire;
- Part 19.200 self-adhesive polyester or polyester-polyamide-imide enamelled round copper wire;
- Part 20.200 polyester or polyester-polyamide imide enamelled round copper wire;
- Part 21.200 Polyester - amide - imide enamelled round copper wire;
- Part 22. 240 aromatic polyimide enamelled round copper wire;
- Part 23. 180 straight welding polyurethane enamelled round copper wire.

This is Part 19 GB/T 6109's. This section identical with IEC 60317-38:2000 "winding wires Product Standards Part 38.200 self-adhesive polyester or polyester-polyamide-imide enamelled round copper wire "version 1.2 (in English).

For ease of use, this section made the following editorial changes.

- Deleted international standards foreword;
- With a decimal point instead of a comma as the decimal point, "";
- According to IEC 60317-0-1:2005 increases the pinhole pilot projects;
- Canceled solvent bonding and the provisions of resolution;
- Removed from Table 2 to 2.000mm 1.600mm excess adhesive load specifications.

This is the first part of the formulation.

This part is proposed by the China Electrical Equipment Industrial Association.

This part of the National Standardization Technical Committee Wire and Cable (SAC/TC213) centralized.

This part of the unit responsible for drafting. Shanghai Electric Cable Research Institute.

Participated in the drafting of this section. Ken Chase Co., Ltd., Chengdu Guoguang Electric Co., Ltd., Guangzhou Wanbao enameled limited the company, Shanghai Yusheng Special Wire Co., Chongming special Electromagnetic Wire Factory, Zhejiang Great Wall Electronic Technology Group.

1 Scope

GB/T 6109 This section provides 200 enamelled round copper wire three requirements of paint. A primer layer of polyester or polyester imide resin as the base, if the chemical characteristics of the original can retain the resin and satisfy all the requirements specified in the wire, the resin may be modified. Intermediate layer Polyamide-imide resin as the base. Topcoat layer is self-adhesive layer is thermoplastic or thermosetting resin-based.

NOTE: chemically-modified resin is a variation of, or contain one or more additives to improve certain properties of the resin or its usage characteristics.

200 represents the thermal level, which requires a minimum temperature index of 200, a heat shock temperature of at least 220 °C.

Corresponding to the temperature index temperature in Celsius is not recommended wire temperature, because it depends on the type of equipment used include Many factors within.

Conductor nominal diameter range specified in this standard are.

-1B Level. 0.050mm and 1.600mm above and below;

-2B Level. 0.050mm and 1.600mm above and below.

Nominal press GB/T 6109.1-2008 prescribed in Chapter 4, the diameter of the conductor.

2 Normative references

The following documents contain provisions which, through reference to GB/T 6109 to the present, constitute provisions of this section. For dated reference documents Member, all subsequent amendments (not including errata content) or revisions do not apply to this section, however, encouraged to reach under this section Parties to research agreement to use the latest versions of these documents. For undated reference documents, the latest versions apply to this section.

Part 1 GB/T 6109.1-2008 enamelled round winding wire. General requirements (IEC 60317-0-1:2005, IDT)

3.1 Definitions, test methods - General

Definitions, test methods, see General GB/T 6109.1-2008 Chapter 3.

If GB/T 6109.1-2008 in this section are contradictory to this section shall prevail.

3.2 Appearance

See GB/T 6109.1-2008 in 3.3.

4 Dimensions

See GB/T 6109.1-2008 in Chapter 4.

5 Resistance

See GB/T 6109.1-2008 in Chapter 5.

GB/T 6109.19-2008/IEC 60317-38:2000