

ICS 29.060.10

CCS K 12



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 7095.5-2008

Replacing GB/T 7095.5-1995

**Enamelled rectangular copper winding wires -- Part 5: Aromatic
polyimide enamelled rectangular copper wire, class 240**

漆包铜扁绕组线 第5部分：240级芳族聚酰亚胺漆包铜扁线

(English Translation)

Issued on: June 13, 2008

Implemented on: March 1, 2009

Issued by: Standardization Administration of China

Table of Contents

Preface	
1 Scope	
2 Normative references	
3 Definitions, test methods and appearance General	
Size 4	
5 Resistance	
Elongation 1	
7 Spring angle	
8 Flexibility and adhesion	
9 Thermal Shock	
10 Softening	
11 Scratch	
12 Solvent	
13 Breakdown Voltage	
14 Insulation Continuity	
15 Temperature index	
16 Anti-freezing agent	
17 Solderable	
18 Heat or solvent bonding	
19 2 dielectric loss factor	
20 Transformer oil resistant	
21 3 Loss	
23 Pinhole test	
30 3 Packaging	

Foreword

GB/T 7095-2008 "flat enamelled copper winding wires" is divided into seven parts.

- Part 1. General requirements;
- Part 2. 120 acetal enamelled copper flat wire;
- Part 3. 155 polyester enamelled copper flat wire;

- Part 4. 180 polyester enamelled copper flat wire;
- Part 5. 240 aromatic polyimide enamelled copper flat wire;
- Part 6. 200 polyester or polyester-imide/polyamide-imide enamelled copper flat wire;
- Part 7. Polyester enamelled copper flat wire.

This section GB/T 7095 Part 5.

This section identical with IEC 60317-47:1997 "Standard winding wires - Part 47. 240 aromatic polyimide enamelled copper flat Line "Version 1.0 (in English).

For ease of use, this section made the following editorial changes.

- Remove the foreword and introduction of international standards;
- With a decimal point '. 'Instead of a comma as the decimal point,' ';
- Increased by 3.2 "look and feel";
- Fixed IEC 60317-47:1997 in the editorial errors, complements Chapter 23, "pinhole test." this section instead of the date of implementation of the GB/T 7095.5-1995.

Section compared with the GB/T 7095.5-1995, major changes in the following.

- According to IEC 60317-47:1997 The structure and content of the GB/T 7095.5-1995 rewritten;
- Modify the thermal class 240, and adjust the "thermal shock", "high-temperature breakdown voltage", "cut through" properties index;
- Conductor nominal size range and heat levels are listed in Chapter 1, "Scope";
- Increased Chapter 3, "Definitions, test methods - General and appearance." this part is proposed by the China Electrical Equipment Industrial Association.

This part of the National Standardization Technical Committee Wire and Cable (SAC/TC213) centralized.

This section is drafted. Shanghai Electric Cable Research Institute, Wuxi City Wire Factory Island, Essex Magnet Wire (Tianjin) Co., Ltd., Wuxi ring Yu Wire Co., Ltd., Shanghai Shen Mao Wire Co., Ltd., Jiangsu Schindler Wire Co., Ltd., four Chuan Jinrui electrician limited liability company.

1 Scope

GB/T 7095 provisions of this section to the aromatic polyimide resin-based single coat enamelled copper flat wire requirements 2401) level.

1) In some countries, such as Canada, the United States, Russia, the product has been

pointed out is 220.

240 represents the thermal level, which requires a minimum temperature index of 240, a heat shock temperature of at least 260 °C.

Corresponding to the temperature index temperature in Celsius is not recommended wire temperature, because it depends on the type of device in use include Many factors within.

This section applies to a conductor nominal size range.

--- Broadside size. minimum 2.00mm, maximum 16.00mm;

--- Narrow size. minimum 0.80mm, maximum 5.60mm.

This section includes Level 1 and Level 2 film thickness enamelled copper flat wire, and is applicable to all specifications conductor.

A combination of size and narrow size broadside and wide/narrow ratio see GB/T 7095.1-2008.

2 Normative references

The following documents contain provisions which, through GB/T reference in this 7095 constitute provisions of this part. For dated reference documents Member, all subsequent amendments (not including errata content) or revisions do not apply to this section, however, encouraged to reach under this section Parties to research agreement to use the latest versions of these documents. For undated reference documents, the latest versions apply to this section.

GB/T 7095.1-2008 flat enamelled copper winding wires - Part 1. General requirements (IEC 60317-0-2:2005, IDT)

3.1 General definitions and test methods

General definitions and test methods see GB/T 7095.1-2008 Chapter 3.

If GB/T 7095.1-2008 in this section are contradictory to this section shall prevail.

3.2 Appearance

See GB/T 7095.1-2008 in Chapter 3.

4 Dimensions

See GB/T 7095.1-2008 in Chapter 4.

5 Resistance

See GB/T 7095.1-2008 in Chapter 5.

6 Elongation

See GB/T 7095.1-2008 in Chapter 6.

GB/T 7095.5-2008/IEC 60317-47:1997