

ICS 29.060.10

CCS K 12



**NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

GB/T 7672.3-2008

Replacing GB/T 7672.4-1987; GB/T 7672.5-1987

**Glass-fiber wound winding wires -- Part 3: Glass-fiber wound
resin or varnish impregnated, bare or enamelled rectangular
copper wire, temperature index 155**

玻璃丝包绕组线第3部分：155级浸漆玻璃丝包铜扁线和玻璃丝包漆包铜扁线

(English Translation)

Issued on: June 30, 2008

Implemented on: May 1, 2009

Issued by: Standardization Administration of China

Table of Contents

What this standard covers	1
Document data	2

What this standard covers

This standard specifies the temperature index of 155, impregnated, bare copper flat wire and impregnated, bare or two enamelled copper flat wire film thickness requirements. Wherein the varnish, for example, a polyester or a polyester -imide resin varnish.

Document data

International classification (ICS): 29.060.10.

Chinese classification (CCS): K12.

Estimated length of the Chinese original: 7,742 words.

Adopted international standard: IEC 60317-32-1990, IDT.

Supersedes the earlier edition GB/T 7672.4-1987; GB/T 7672.5-1987.