

**CHEMICAL INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

HG/T 2051.1-2019

Replacing HG/T 2051.1-2013

Glass-lined agitators - Anchor agitators

搪玻璃搅拌器 锚式搅拌器

(English Translation)

Issued on: December 24, 2019

Implemented on: July 1, 2020

**Issued by: Ministry of Industry and Information Technology of the
People's Republic of China**

Table of Contents

Foreword

Foreword

SAC/TC 72 is in charge of this English translation. In case of any doubt about the contents of English translation, the Chinese original shall be considered authoritative.

This standard is drafted in accordance with the rules given in the GB/T 1.1-2009.

This standard replaces the HG/T 2051.1-2013 Glass-lined agitator anchor type in whole.

In addition to a number of editorial changes, the following technical deviations have been made with respect to the HG/T 2051.1-2013:

- - Removed specifications for agitator of mixing vessel with 400L nominal capacity (see Table 1 of 2013 edition);
- - The dimensions of blade in Table 1 of the original standard were revised from the original "t" to "t₂ x t₄", i.e., from the original "38, 48, 60, 86, 97" to "38x 20, 48 x 25, 60 x 30, 86 x 43, 97x 50"(see Table 1, and Table 1 of 2013 edition);
- - Revised the size of L4 in Table 2 of the original standard from the original "80, 100, 110, 120" to "60, 90, 100, 110" (see Table 2, and Table 2 of 2013 edition);
- - Revised the size of L3 in Table 3 of the original standard from the original "20, 20" to "36, 36, " (see Table 3, and Table 3 of 2013 edition)
- - Revised the size of L33 in Table 3 of the original standard from the original "34, 34" to "50, 50" (see Table 3, and Table 3 of 2013 edition);
- - Revised the size of L3 in Table 4 of the original standard from the original "18, 18" to "26, 30" (see Table 4, and Table 4 of 2013 edition);
- - Revised the size of L33 in Table 4 of the original standard from the original "32, 32" to "40, 44" (see Table 4, and Table 4 of 2013 edition);
- - Deleted the structure type, main size and basic parameters of BII-type shaft end;
- - The shaft end code "BI-type" was revised to "B-type" (see 3.2,3.3, and Clause 3.2, 3.3 of 2013 edition);
- - Added the structure type, main size and basic parameters of the D-type shaft end (see Figure 5, Table 5);

- - Deleted Clause 4.4 " Welding seams shall not have obvious roughness or unevenness "
and Clause 4.5 ""Blades shall not have obvious processing imprint " in the original standard
(see Clause 4.4 and Clause 4.5 of 2013 edition).

chinastandards.org - PREVIEW