

ICS 23.040.70
CCS G 42

HG

**CHEMICAL INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

HG/T 2184-2008

Replacing HG/T 2184-1991

**Rubber hoses, textile-reinforced, for general-purpose water
applications**

通用输水织物增强橡胶软管

(English Translation)

Issued on: April 23, 2008

Implemented on: October 1, 2008

Issued by: Ministry of Industry and Information Technology

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard specifies the three types suitable temperature range is $-25^{\circ}\text{C} \sim +70^{\circ}\text{C}$, the maximum working pressure is 2.5MPa universal fabric reinforced rubber hose water requirements. These hoses do not apply to transport drinking water, washing water and special agricultural machinery, nor be used as a fire hose or foldable water pipes. These hoses can be used to reduce the freezing point of water conveying additive.

Document data

International classification (ICS): 23.040.70.

Chinese classification (CCS): G42.

Estimated length of the Chinese original: 8,885 words.

Adopted international standard: ISO 1403-2005, MOD.

Supersedes the earlier edition HG/T 2184-1991.

Standards quoted by this document

GB/T 528; GB/T 2941; GB/T 5563; GB/T 5564-2006; GB/T 5565-2006; GB/T 7528; GB/T 9573; GB/T 9575; HG/T 2185; HG/T 2869-1997; ISO 188-1998; ISO 8033