Chinastandards.org

ICS 79.080
CCS B 70

LY

INDUSTRY STANDARD OF THE PEOPLE'S REPUBLIC OF CHINA

LY/T 1330-2011

Antistatic wood-based moveable floor

抗静电木质活动地板

(English Translation)

Issued on: June 19, 2023 **Implemented on: November 1, 2023**

Issued by: State Forestry and Grassland Administration

Preview: page 1 of 4 shown, 14 in the full document. Complete English PDF, instant download:
https://chinastandards.org/standards/ly-t-1330-2011

Chinastandards.org

Table of Contents

Foreword

1 Scope

2 Normative references

3 Terms and definitions

Foreword

This document is in accordance with the provisions of GB/T 1.1-2020 "Guidelines for standardization work Part 1: Structure and drafting rules for standardization documents" Drafting.

This document replaces LY/T 1330-2011 "Antistatic Wooden Raised Floor". Compared with LY/T 1330-2011, in addition to structural adjustments and in addition to editorial changes, the main technical changes are as follows.

--- Changed the scope (see Chapter 1, Chapter 1 of the 2011 edition);

--- Changed the definitions of "antistatic wooden raised floor", "system resistance", "concentrated load", "rated concentrated load" and "rolling load" (see 3.1, 3.2, 3.5, 3.6, 3.7, 3.1, 3.2, 3.6, 3.7, 3.8 of the 2011 version), delete "load point" (see 3.5 of the 2011 version);

--- Added "Structure" (see Chapter 4);

--- Changed the requirements for "net length deviation" and "thickness deviation" in "Requirements" (see Table 2, Table 1 of the 2011 edition);

--- Changed the content of "Appearance Quality" in "Requirements" and added the appearance quality requirements of fasteners and support systems (see 5.2, 2011 Version 4.2);

--- Changed the names of "wheel wear" and "electrical properties" in "physical and chemical properties" (see Table 3, Table 4, 6.4.2, 6.3.4, 2011 version of the table 2,5.2.6,5.2.10);

--- Deleted "surface wear resistance", "castor wear resistance", "impact resistance", "concentrated load" and "rolling load" in "physical and chemical properties" (see 2011 edition

Table 2) includes "surface wear resistance", "castor wear resistance", "impact resistance", "concentrated load" and "rolling load" in the "mechanical properties"

"capable" (see 5.4);

Preview: page 2 of 4 shown, 14 in the full document. Complete English PDF, instant download:
https://chinastandards.org/standards/ly-t-1330-2011

--- Added "support system load performance" and its test method, and included the relevant content in "mechanical properties" (see Table 4, 6.4.6);

--- Deleted "combustion performance" in "physical and chemical properties", listed "combustion performance" independently, and changed the description of its requirements and test methods (See Table 2, 5.2.11 of 5.5, 6.5, 2011 edition);

--- Added "Concentration limits of volatile organic compounds" and its test methods, and included relevant content in "Physical and chemical properties" (see Table 3,6.3.6);

--- Added "appearance" and its inspection method (see 5.2, 6.2);

--- Added requirements for physical and chemical properties test specimens (see Table 5);

--- Deleted the requirements and test methods for "surface resistance to cold and hot cycles" (see 5.2.3 of the 2011 edition);

--- Changed the test method of "water absorption thickness expansion rate" (see 6.3.2, 5.2.2 of the 2011 edition);

--- Changed the test method of "surface contamination resistance" (see 6.3.3, 5.2.4 of the 2011 edition);

--- Changed the test method of "antistatic performance" (see 6.3.4, 5.2.10 of the 2011 edition);

--- Changed the test method of "formaldehyde emission" in "physical and chemical properties" (see 6.3.5, 5.2.12 of the 2011 edition);

--- Deleted the "test environment" of "wear resistance of castors" (see 5.2.6.1 of the 2011 edition), and changed the castor wear resistance of castors.

The hardness is (95 ± 5) (see 6.4.2.1, 5.2.6.1 of the 2011 edition);

--- Changed the test method of "impact resistance" (see 6.4.3, 5.2.7 of the 2011 edition);

--- Changed the description of the "concentrated load" test method (see 6.4.4, 5.2.8 of the 2011 edition);

--- Changed the description of the "rolling load" test method (see 6.4.5, 5.2.9 of the 2011 edition);

--- Deleted "Formaldehyde emission and water absorption thickness expansion rate test in physical and chemical performance test" and "System height test" in "Factory inspection" (6.1.1 of the 2011 edition), added "antistatic performance test" (see 7.1.1);

--- Changed the contents of "Type Inspection", "Sampling Plan and Judgment Principles" and "Result Judgment" in "Inspection Rules" (see 7.1.2, 7.3, 7.4, 6.1.2, 6.3, 6.4 of 2011 version).

Preview: page 3 of 4 shown, 14 in the full document. Complete English PDF, instant download:
https://chinastandards.org/standards/ly-t-1330-2011

1 Scope

This document specifies the structure, requirements, inspection methods, inspection rules, as well as marking, packaging, transportation and storage of antistatic wooden raised floors.

Save and so on.

This document is suitable for computer rooms, communication hub rooms, financial data centers, power dispatching centers and other places that require anti-static and wiring.

Raised floor in the venue.

2 Normative references

The contents of the following documents constitute the essential clauses of this document through normative references in this document.

For referenced documents without a date, only the version corresponding to that date applies to this document; for referenced documents without a date, the latest version (including all amendments) applies to this document.

GB/T 2828.1-2012 Sampling procedures for inspection by attributes Part 1: Sampling for batch inspection based on acceptance quality limit (AQL) plan GB/T 5779.1 Fastener surface defects - General requirements for bolts, screws and studs GB 8624-2012 Classification of combustion performance of building materials and products GB/T 8626-2007 Test methods for flammability of building materials GB/T 17657-2013 Test methods for physical and chemical properties of wood-based panels and veneer wood-based panels GB 18580 Limits of formaldehyde emission from artificial boards and their products for interior decoration and renovation GB/T 29899-2013 Test method for emission of volatile organic compounds from wood-based panels and their products - Small emission chamber method GB 50222-2017 Code for fire protection design of interior decoration of buildings

3 Terms and definitions

The following terms and definitions apply to this document.

A detachable raised floor with antistatic function made of wood material.

System resistance the resistance between the floor surface and the grounding of the supporting system.

System height the distance from the upper surface of the floor to the mounting plane.

Installation height settingheight the distance from the underside of the floor to the mounting plane.

Preview: page 4 of 4 shown, 14 in the full document. Complete English PDF, instant download:
https://chinastandards.org/standards/ly-t-1330-2011