

ICS 97.040.99  
CCS Y 63

**QB**

**LIGHT INDUSTRY STANDARD OF THE  
PEOPLE'S REPUBLIC OF CHINA**

**QB/T 5199-2017**

---

**Disinfecting tableware cabinet**

食具消毒柜

**(English Translation)**

**Issued on: November 7, 2017**

**Implemented on: April 1, 2018**

---

**Issued by: Ministry of Industry and Information Technology**

## Table of Contents

|                                         |   |
|-----------------------------------------|---|
| What this standard covers .....         | 1 |
| Document data .....                     | 2 |
| Standards quoted by this document ..... | 3 |

### What this standard covers

This standard specifies the terms and definitions, classification and nomenclature, requirements, test methods, inspection rules and signs, packaging, transportation, and storage of tableware disinfection cabinets. This standard applies to single-phase appliance rated voltage does not exceed 250 V, other appliances rated voltage does not exceed 480 V of household and similar use of tableware disinfection cabinet (hereinafter referred to as disinfection cabinet). Disinfection cabinet uses electric energy as the main energy source. Its disinfection methods include electric heating method, ozone method, ultraviolet radiation (can only be used as an auxiliary) and the above-mentioned several disinfection methods. The disinfection cabinets of other disinfection methods can also be used as reference. This standard does not apply to: 1. Disinfection cabinets that rely only on ultraviolet radiation; 2. Other disinfection cabinets that do not use utensils disinfection as their main purpose, such as towel disinfection cabinets; 3. Disinfection for special occasions

### Document data

International classification (ICS): 97.040.99.

Chinese classification (CCS): Y63.

Estimated length of the Chinese original: 12,189 words.

### Standards quoted by this document

GB/T 191; GB/T 1019; GB/T 2423.3; GB/T 2423.17; GB 4706.1; GB/T 5296.1; GB/T 5296.2; GB/T 9286; GB/T 17841; GB 17988; GB/T 19258-2012; GB 28232-2011; JB/T 4088-2012