

ICS 17.060
CCS A52

SN

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

SN/T 2389.12-2012

**Rules for the measurement survey of import and export
commodities. Part 12: Static measurement of asphaltum on
board**

(English Translation)

Issued on: October 23, 2012

Implemented on: May 1, 2013

Issued by: General Administration of Customs

Table of Contents

- Foreword
- 1 Scope
- 2 Normative references
- 3 Terms and Definitions
- 4 Basic requirements
- 4.1 Working conditions

Foreword

SN/T 2389 "Import and Export container weight of order" is divided into 12 parts.

- Part 1. Terminology
- Part 2. Animal and vegetable oils shore vertical metal tank static weight
- Part 3. Orimulsion shore vertical metal tank static weight
- Part 4. LPG cabin static weight
- Part 5. shore oil vertical metal tank static weight
- Part 6. determination line between the shore boat fullness
- Part 7. shore vertical metal pressure tanks (non-refrigerated) level automatic measurement
- Part 8. Orimulsion Cabin static weight
- Part 9. cargo ship line was estimated volume
- Part 10. Static liquid chemicals cabin weight
- Part 11. Liquid chemicals shore vertical metal tank static weight
- Part 12. asphalt cabin static weight this section SN/T 2389 Part 12.

This section drafted in accordance with GB/T 1.1-2009 given rules.

This section proposed and managed by the National Certification and Accreditation Administration Committee.

1 Scope

This section SN/T 2389 provisions of the import and export of asphalt cabin static weight of the methods, procedures and requirements.

This section applies to the import and export of asphalt static weight in the cabin.

2 Normative references

The following documents for the application of this document is essential. For dated references, only the dated version suitable for use herein Member. For undated references, the latest edition (including any amendments) applies to this document.

Analyzing and processing GB/statistical processing and interpretation of normal sample values T 4883 data GB/T 8170 repair value expressed about the rules and limit values and judgment GB/T 8927 Petroleum and liquid petroleum products - Temperature measurement - Manual methods GB/T 8928 solid and semi-solid petroleum asphalt densitometry GB/T 11147 bitumen sampling method SN/T 0993 import and export commodities by weight liquid product identification procedures static weight SN/T 2389.1 weight regulations Import and Export containers - Part 1. Terminology

3 Terms and Definitions

Terms and definitions SN/T 2389.1 and SN/T 0993 defined apply to this document.

4.1.1 Dipstick

Dipstick should be within the validity of the measurement of qualified and should be intact.

4.1.2 Thermometer

Measuring cabin asphalt temperature thermometer, preferably portable electronic thermometer, you can also use glass box thermometer shall comply with mild high Requirements under higher viscosity conditions of use and shall be approved through qualified and qualified calibration test of the department in the period.

4.1.3 Densitometer

Density meter should be within the validity of the measurement of qualified and intact.

4.1.4 Sampler

Sampling should be stainless steel, copper or aluminum material, sampler material should not react chemically with asphalt and bitumen influence