

ICS 75.180.10; 77.040.20
CCS H 26;H26

SY

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

SY/T 6858.6-2016

Replacing SY/T 6508-2000

**Nondestructive testing method for OCTG. Part6-Liquid
penetrant flaw detection for nonferrous magnetic thread**

油井管无损检测方法 第6部分：非铁磁体螺旋渗透检测

(English Translation)

Issued on: January 7, 2016

Implemented on: June 1, 2016

Issued by: National Development and Reform Commission

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard specifies the detection principle, operator requirements, detection methods, detection detectors and devices, detection sensitivity and calibration, and detection procedures for non-ferromagnetic oil well pipe thread penetration testing. This standard applies to non-ferromagnetic oil well pipes such as non-magnetic drill collars, titanium alloy drill pipe, aluminum alloy drill pipe and other thread penetration testing, also applies to ferromagnetic oil well pipe thread penetration test to find the thread parts such as fatigue crack surface opening defects Or defects.

Document data

International classification (ICS): 75.180.10; 77.040.20.

Chinese classification (CCS): H26;H26.

Estimated length of the Chinese original: 13,162 words.

Supersedes the earlier edition SY/T 6508-2000.

Standards quoted by this document

GB/T 5097; GB/T 9445; GB 11533; JB/T 6064