Chinastandards.org

ICS 75.180.10
CCS E92

SY

INDUSTRY STANDARD OF THE PEOPLE'S REPUBLIC OF CHINA

SY/T 6915.3-2019

Petroleum and natural gas drilling and production equipment Flow control system for eccentric working cylinder Part 3: Delivery head, salvage head, fishing device and positioning locking mechanism

石油天然气钻采设备 偏心工作筒流量控制系统 第3部分：偏心工作筒用投送头、打捞头、投捞器及定位锁紧机构

(English Translation)

Implemented on: May 1, 2020

Issued by: National Energy Administration

Preview: page 1 of 4 shown, 26 in the full document. Complete English PDF, instant download:
https://chinastandards.org/standards/sy-t-6915-3-2019

Chinastandards.org

Table of Contents

[Preview only]
1 Scope
1.2 Definition of terms
2 Normative references
2.1 General requirements
2.2 Pressure-drop limitations and piping configurations
2.3 Inlet stresses that originate from static loads in the discharge piping
2.4 Inlet stresses that originate from discharge reaction forces
2.5 Isolation valves in inlet piping
2.6 Rupture disk devices in combination with pressure relief valves
2.7 Process laterals connected to inlet piping of pressure relief valves
2.8 Turbulence in pressure relief device inlets
3 Terms and definitions
3.2 Safe disposal of relieving fluids
3.3 Back pressure limitations and sizing of pipe
3.4 Considerations for pilot-operated pressure relief valves
3.5 Stresses that originate from discharge piping
3.6 Isolation valves in the discharge piping
4 Isolation valves in pressure relief piping
4.1 Determination of relief requirements
4.2 Relieving pressure
4.3 Sizing for gas or vapor relief
4.4 Examples of isolation valve installations
4.5 Sizing for liquid relief: relief valves requiring liquid capacity certification
4.6 Sizing for liquid relief: relief valves not requiring liquid capacity certification
4.7 Sizing for two-phase liquid/vapor relief
4.8 Sizing for rupture disk devices
5 Bonnet or pilot vent piping
5.1 Conventional pressure relief valves
5.2 Balanced bellows pressure relief valves
5.3 Balanced piston pressure relief valve
5.4 Pilot-operated pressure relief valves

Preview: page 2 of 4 shown, 26 in the full document. Complete English PDF, instant download:
https://chinastandards.org/standards/sy-t-6915-3-2019

5.5 Thickness calculation of planar insulation layer
6 Drain piping
6.1 Installation conditions that require drain piping
6.2 Safe practice for installation of drain piping
6.3 SPM Location and Spatial Requirements
6.4 Other materials
6.5 Transportation, storage and custody of materials
7 Pressure relief device location and position
7.1 Inspection and maintenance
7.2 Proximity to pressure source
7.3 Proximity to other equipment
7.4 Mounting position
7.5 Test or lifting levers
7.6 Heat tracing and insulation
8 Bolting and gasketing
8.1 Care in installation
8.2 Proper gasketing and bolting for service requirements
8.3 Welding
8.4 Quality Control and Inspection
9 Multiple pressure relief valves with staggered settings
9.2 Installation of Mooring Foundation
9.3 Laying of Mooring Lines
9.4 Hook-up of Mooring Lines

1 Foreword

SY/T 6915.3-2019 was issued by National Energy Administration on 4 November 2019 and has been in force since 1 May 2020.

It is one of 4 parts of the SY/T 6915 series.

The SY/T prefix marks a recommended standard. It is not law in itself: it becomes binding when a contract names it, when a regulation or a mandatory standard refers to it, or when a producer declares conformity with it.

Preview: page 3 of 4 shown, 26 in the full document. Complete English PDF, instant download:
https://chinastandards.org/standards/sy-t-6915-3-2019

2 Scope Preview

SY/T 6915.3-2019 falls under ICS 75.180.10, in the field of petroleum and related technologies.

This catalogue holds 482 other SY/T standards in that field.

In this catalogue, SY/T standards carry edition years from 1973 to 2025.

3 About this standard

Sector: Oil & Gas Industry Standard (Recommended)

Issued by: National Energy Administration

English translation: about 26 pages (approximate)

Chinese original: about 38,343 characters

4 Related standards

Other parts of this standard:

SY/T 6915.1-2012 - Petroleum and natural gas industries. Drilling and production equipment. Part 1: Side-pocket mandrel

SY/T 6915.2-2017 - Petroleum and natural gas drilling and production equipment-. Flow control systems for side-pocket mandrel. Part 2: Flow-control device for side-pocket mandrels

SY/T 6915.4-2020 - Petroleum and natural gas drilling equipment. Eccentric working cylinder flow control system - Part 4: Operating regulations for eccentric working cylinder and related equipment

Standards on related subjects:

SY/T 5164-2016 - Roller cone drill bits

SY/T 5324-2013 - Pre-Stress Insulated Tubing

SY 0007-1999 - Design standard of corrosion control for steel pipeline and storage tank

5 Classification and status

International classification (ICS): 75.180.10

Chinese Standard Classification (CCS): E 92

Prefix SY/T: recommended standard.

Preview: page 4 of 4 shown, 26 in the full document. Complete English PDF, instant download:
https://chinastandards.org/standards/sy-t-6915-3-2019