Chinastandards.org

ICS 91.060.50
CCS Q71

WB

WB/T 1047-2012

Installation specification of wood door

木质门安装规范

(English Translation)

Issued on: March 24, 2012 **Implemented on: July 1, 2012**

Issued by: National Development and Reform Commission of the People's Republic of China

Preview: page 1 of 3 shown, 5 in the full document. Complete English PDF, instant download:
https://chinastandards.org/standards/wb-t-1047-2012

Chinastandards.org

Table of Contents

Foreword

1 Scope

2 Normative references

3 Terms and definitions

4 Basic requirements

4.1 Preparation before construction

Foreword

This standard was drafted in accordance with the rules given in GB/T 1.1-2009.

This standard proposed by the China Federation of Logistics and Purchasing and centralized.

1 Scope

This standard specifies the installation of indoor wooden doors basic requirements and acceptance criteria.

This standard applies to the installation and acceptance of indoor wooden doors.

2 Normative references

The following documents for the application of this document is essential. For dated references, only the dated version applies to this article Pieces. For undated references, the latest edition (including all amendments) applies to this document.

WB/T 1024-2006 wooden door

3 Terms and definitions

WB/T 1024-2006 defined and the following terms and definitions apply to this document.

Hole size net size fulsizeofhole Floor, wall finish floor, wall tiles and other pavement after the hole size, including the hole depth, hole width, hole height three dimensions.

The width of the hole fulwidthofhole the smallest horizontal hole size.

The net thickness of the hole fulthicknessofhole the minimum size of the hole wall after treatment.

Preview: page 2 of 3 shown, 5 in the full document. Complete English PDF, instant download:
https://chinastandards.org/standards/wb-t-1047-2012

The height of the hole fulhighnessofhole the minimum vertical size of the hole.

4.1.1 Hole measurement

Wooden doors shall be measured to the customer's opening before design, fabrication and installation. Measurement should be completed after the renovation of the surface, the wall after the foot material Inch for the measurement basis; if the ground, wall construction is not completed, should be reserved for the thickness of decoration materials.

4.1.1.1 Measurement of the width of the hole

Horizontal measurement hole size, should be selected 5 measurement points for measurement, of which the minimum width of the hole (diameter) size; if the remaining 4 Point of the measured value is greater than 20mm, you can request the hole for dressing.

Preview: page 3 of 3 shown, 5 in the full document. Complete English PDF, instant download:
https://chinastandards.org/standards/wb-t-1047-2012