

ICS 65.160
CCS X 89

YC

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

YC/T 323-2009

**Safety signs of cigarette enterprise. Specification for use
(English Translation)**

Issued on: December 14, 2009

Implemented on: March 1, 2010

Issued by: State Tobacco Monopoly Administration

Table of Contents

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Security identity management requirements

Use of technology security identity of claims 2

6 Industrial pipelines using technology to identify basic colors, symbols and safety signs to identify the requirements of

Appendix A (informative) Fire safety signs Example

Annex B (informative) Examples of identification factory road traffic safety

Annex C (informative) Examples of identification of dangerous chemicals

Annex D (informative) Examples of identification of harmful factors in job security

Appendix E (normative) Safety signage size

Foreword

The Standard Appendix A, Appendix B, Appendix C, Appendix D and Appendix E is an informative annex.

This standard was proposed by the State Tobacco Monopoly Bureau.

This standard by the National Standardization Technical Committee on Tobacco Enterprise Technical Committee (SAC/TC144/SC4) centralized.

This standard was drafted. Hongta Tobacco (Group) Co., Ltd., the State Tobacco Monopoly Bureau of Economic Operation Division, China Tobacco Yunnan Industrial Corporation, China Tobacco Industry Development Center, Anhui tobacco industry, tobacco industry in Shandong, Hubei tobacco industry limited liability company, Guangxi Tobacco Industry limited liability company.

1 Scope

This standard specifies the requirements for the use of cigarette production enterprise security identity.

This standard applies to cigarette manufacturers, tobacco companies may refer to other.

2 Normative references

The following documents contain provisions which, through reference in this standard and become the standard terms. For dated references, subsequent Amendments (not including errata content) or revisions do not apply to this standard, however, encourage the parties to the agreement are based on research Whether the latest versions of these documents. For undated reference documents, the latest versions apply to this standard.

GB 2893 Safety colors GB/T 2893.1 Graphical symbols - Safety colors and safety signs - Part 1. workplaces and public areas for safety signs set Accounting principles GB 2894 Safety Signs and use guidelines GB 5768 (all parts), road traffic signs and markings Basic identification colors GB 7231 industrial piping, identifying symbols and safety identification GB 13495 fire safety signs GB 15630 fire safety signs GB Z158 workplace occupational hazard warning labels GA480 (all parts), fire safety signs general technical conditions YC/T 312 cigarette industry enterprises Safety Evaluation Guidelines

3 Terms and Definitions

The following terms and definitions apply to this standard.

Relative isolation from the outside world, import and export limited natural ventilation bad enough for a person to enter and engage in unconventional, non-continuous operation is limited space. Including tanks, boiler furnace, flue gas tank, underground trench, sewers, cesspools and septic tanks.

4 Security identity management requirements

Security identity management requirements should be consistent with the requirements of Table 1.

Table 1 security management requirements identified

Name Requirements

Management requirements 1. Established and implemented security identity management system.

2. In accordance with the requirements of this standard setting security identity should be consistent with GB 2893, GB/T 2893.1, GB 2894, GB 5768 (all parts), GB 7231, GB 13495, GB 15630, GB Z158 and GA480 (all parts) requirements.

3. After the security flag setting, there should be no potential risk of causing any harm to the human body and does not affect product quality.

4. Security identity should not replace the safety facilities.

5. The implementation of technological innovation, should be unified planning, set the

matching security identity.

6. Supervise the construction side should set the security identity transformation in the construction site.