

ICS 33.180.10
CCS M 33

YD

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

YD/T 1588.3-2009

**Measurement Methods for Characteristics of Optical Fibre
Cable Line. Part 3: Polarization Mode Dispersion for Optical
Cable Link**

光缆线路性能测量方法 第3部分：链路偏振模色散

(English Translation)

Issued on: June 15, 2009

Implemented on: September 1, 2009

Issued by: Ministry of Industry and Information Technology

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard specifies the optical fiber transmission link PMD measurement methods, measurement systems, measurement procedures, calculation methods and results processing. This standard applies to silica-based single-mode fiber optic cable link PMD measurement, from GB/T 15972. 10-2008 specified class B consisting of optical fiber transmission link. They can be interconnected already laid optical cable splice, the optical communication transceiver may be an optical path between the devices, or a part of it. The link may include other optical components such as optical amplifiers, WDM devices, etc. combiner.

Document data

International classification (ICS): 33.180.10.

Chinese classification (CCS): M33.

Estimated length of the Chinese original: 29,245 words.

Standards quoted by this document

GB/T 15972.10-2008